

# 屋内照明器具特性

|         |                         |           |
|---------|-------------------------|-----------|
| 品番 (品名) | NSEK47622J + NNL4200EVT |           |
| 光源      | LED3000_85_2330 ×1      | 2330.0 lm |
| 管理番号    | K0145987 (0) DB 1       |           |
| BZ分類    | BZ5 / 1.4 / BZ4         |           |

|        |                  |         |                  |      |     |     |      |      |     |     |      |      |    |    |      |      |    |    |     |     |
|--------|------------------|---------|------------------|------|-----|-----|------|------|-----|-----|------|------|----|----|------|------|----|----|-----|-----|
| 器具効率   | 100 %            | 天井      | 80 %             |      |     |     | 70 % |      |     |     | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|        | 上方光束<br>0 %      |         | 反射率              | 70   | 50  | 30  | 10   | 70   | 50  | 30  | 10   | 70   | 50 | 30 | 10   | 70   | 50 | 30 | 10  | 0 % |
| 下方光束   | 100 %            | 床       |                  | 10 % |     |     |      | 10 % |     |     |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
| 室指数    | 照明率 ( X0.01 )    |         |                  |      |     |     |      |      |     |     |      |      |    |    |      |      |    |    |     | ZCM |
| 保守率    | 良                | 0.81    | 0.6              | 57   | 45  | 37  | 31   | 56   | 44  | 37  | 31   | 53   | 43 | 36 | 31   | 51   | 42 | 36 | 31  | 29  |
|        | 中                | 0.77    | 0.8              | 67   | 56  | 48  | 42   | 66   | 55  | 47  | 42   | 63   | 53 | 47 | 42   | 60   | 52 | 46 | 41  | 39  |
|        | 否                | 0.68    | 1.0              | 74   | 63  | 56  | 50   | 72   | 62  | 55  | 50   | 69   | 61 | 54 | 49   | 67   | 59 | 54 | 49  | 47  |
|        |                  |         | 1.25             | 80   | 70  | 63  | 58   | 78   | 69  | 63  | 57   | 75   | 68 | 62 | 57   | 73   | 66 | 61 | 56  | 54  |
| 下方投影面積 | c m <sup>2</sup> |         | 1.5              | 84   | 76  | 69  | 63   | 83   | 75  | 68  | 63   | 79   | 73 | 67 | 63   | 77   | 71 | 66 | 62  | 60  |
|        | 等価発光面積           |         | c m <sup>2</sup> | 2.0  | 90  | 83  | 77   | 72   | 88  | 82  | 76   | 72   | 85 | 80 | 75   | 71   | 82 | 78 | 74  | 70  |
| 取付高さ   | 器具間隔最大限          |         | 2.5              | 93   | 87  | 82  | 78   | 92   | 86  | 82  | 77   | 89   | 84 | 80 | 77   | 86   | 82 | 79 | 76  | 73  |
|        | 横方向 (A)          | 縦方向 (B) | 3.0              | 96   | 91  | 86  | 82   | 94   | 90  | 85  | 82   | 91   | 87 | 84 | 81   | 89   | 85 | 82 | 80  | 77  |
| 1.5m   | 2.01 m           | 2.15 m  | 4.0              | 99   | 95  | 91  | 88   | 98   | 94  | 90  | 87   | 95   | 92 | 89 | 86   | 92   | 89 | 87 | 85  | 82  |
| 2      | 2.66             | 2.71    | 5.0              | 101  | 97  | 94  | 92   | 99   | 96  | 93  | 91   | 97   | 94 | 92 | 89   | 94   | 92 | 90 | 88  | 85  |
| 2.5    | 3.3              | 3.29    | 7.0              | 103  | 100 | 98  | 96   | 102  | 99  | 97  | 95   | 99   | 97 | 95 | 94   | 97   | 95 | 93 | 92  | 89  |
| 3      | 3.94             | 3.88    | 10.0             | 105  | 103 | 101 | 99   | 103  | 102 | 100 | 99   | 101  | 99 | 98 | 97   | 98   | 97 | 96 | 95  | 92  |

