

# 屋内照明器具特性

品番 (品名)	NTN81384 + NTN81997	
光源	LED2700_70_1880 x1	1880.0 lm
管理番号	K0163042 (0) DR1	
BZ分類	BZ5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	12 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	88 %	室指数	照明率 ( X0.01 )																				ZCM
保守率	良 中 否	0.69	0.6	5.3	4.1	3.3	2.8	5.1	4.0	3.2	2.7	4.8	3.8	3.1	2.6	4.5	3.6	3.0	2.6	2.3			
		0.67	0.8	6.3	5.1	4.3	3.7	6.1	5.0	4.2	3.6	5.6	4.7	4.0	3.5	5.3	4.5	3.9	3.4	3.1			
			1.0	6.9	5.8	5.0	4.4	6.7	5.6	4.9	4.3	6.2	5.3	4.7	4.2	5.8	5.1	4.5	4.0	3.7			
		0.63	1.25	7.5	6.5	5.7	5.1	7.2	6.3	5.6	5.0	6.8	6.0	5.3	4.8	6.3	5.6	5.1	4.7	4.3			
下方投影面積	c m <sup>2</sup>	1.5	7.9	7.0	6.2	5.6	7.6	6.8	6.1	5.5	7.1	6.4	5.8	5.3	6.7	6.1	5.6	5.1	4.7				
		2.0	8.5	7.7	7.0	6.4	8.2	7.5	6.8	6.3	7.7	7.1	6.5	6.1	7.2	6.7	6.2	5.9	5.4				
取付高さ	器具間隔最大限		2.5	8.8	8.1	7.5	7.0	8.6	7.9	7.4	6.9	8.0	7.5	7.0	6.6	7.5	7.1	6.7	6.4	5.9			
	横方向 (A)	縦方向 (B)	3.0	9.1	8.5	7.9	7.4	8.8	8.2	7.7	7.3	8.3	7.8	7.4	7.0	7.8	7.4	7.0	6.7	6.2			
1.5m	2.01 m	2.13 m	4.0	9.4	8.9	8.4	8.0	9.1	8.7	8.3	7.9	8.6	8.2	7.9	7.6	8.1	7.8	7.5	7.2	6.7			
2	2.64	2.68	5.0	9.6	9.2	8.8	8.4	9.3	8.9	8.6	8.3	8.8	8.5	8.2	7.9	8.3	8.1	7.8	7.6	7.0			
2.5	3.29	3.25	7.0	9.9	9.5	9.2	8.9	9.6	9.3	9.0	8.7	9.1	8.8	8.6	8.4	8.6	8.4	8.2	8.0	7.4			
3	3.92	3.83	10.0	10.0	9.8	9.6	9.3	9.8	9.6	9.3	9.1	9.3	9.1	8.9	8.7	8.8	8.6	8.5	8.4	7.8			

