

屋内照明器具特性	
品番 (品名)	NTN81520
光源	LED5000_70_620 ×1 620.0 lm
管理番号	K0193766 (0) DR 1
BZ分類	BZ5

器具効率		100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.69	0.6	54	42	34	28	52	41	33	28	49	39	32	27	46	37	31	27	24	
			0.67	0.8	64	52	44	38	61	50	43	37	58	48	41	36	54	46	40	35	32	
			0.63	1.0	70	59	51	45	68	57	50	44	63	55	48	43	60	52	46	42	38	
			0.63	1.25	76	65	58	52	73	64	57	51	69	61	55	50	65	58	53	48	45	
下方投影面積		cm ²	1.5	80	70	63	57	77	69	62	56	73	65	59	55	68	62	57	53	49		
			等価発光面積	cm ²	2.0	85	77	71	65	83	75	69	64	78	72	67	62	74	69	64	60	56
取付 高さ	器具間隔最大限			2.5	89	82	76	71	86	80	74	70	82	76	72	68	77	73	69	65	61	
	横方向 (A)		縦方向 (B)	3.0	91	85	80	75	89	83	78	74	84	79	75	71	80	76	72	69	64	
1.5m	1.94 m	1.89 m	4.0	95	90	85	81	92	88	83	80	88	84	80	77	83	80	77	74	69		
2	2.58	2.49	5.0	97	93	89	85	94	90	87	84	90	86	83	81	85	83	80	78	73		
2.5	3.25	3.1	7.0	99	96	93	90	97	94	91	88	92	90	87	85	88	86	84	82	77		
3	3.87	3.7	10.0	101	99	96	94	99	97	94	92	94	92	91	89	90	88	87	85	80		

