

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XF X440NJN                   |
| 光源       | LED5000_85_3460 ×1 3460.0 lm |
| 管理番号     | K0193780 ( 0 ) DB1           |
| BZ分類     | BZ4/6.0/BZ5                  |

| 器具効率     |           | 100 %           | 反射率             | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |   |   |  |   |
|----------|-----------|-----------------|-----------------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|---|---|--|---|
|          |           |                 |                 | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |   |   |  |   |
|          |           |                 |                 | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |   |   |  |   |
| 上方光束     |           | 12 %            | 室指数             | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  | Z | C |  | M |
| 下方光束     |           | 88 %            |                 |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |   |   |  |   |
| 保守率      |           | 良<br>中<br>否     | 0.83            | 0.6           | 59   | 48 | 41 | 36 | 57   | 47 | 40 | 35 | 54   | 45 | 39 | 35 | 51   | 43 | 38 | 34 | 31  |  |   |   |  |   |
|          |           |                 | 0.81            | 0.8           | 68   | 58 | 51 | 46 | 66   | 57 | 50 | 45 | 62   | 54 | 49 | 44 | 59   | 52 | 47 | 43 | 40  |  |   |   |  |   |
|          |           |                 | 0.77            | 1.0           | 75   | 65 | 58 | 53 | 72   | 64 | 57 | 52 | 68   | 61 | 55 | 51 | 64   | 58 | 53 | 50 | 46  |  |   |   |  |   |
|          |           |                 |                 | 1.25          | 80   | 71 | 65 | 60 | 78   | 70 | 64 | 59 | 73   | 67 | 61 | 57 | 69   | 63 | 59 | 56 | 52  |  |   |   |  |   |
| 下方投影面積   |           | cm <sup>2</sup> |                 | 1.5           | 84   | 76 | 70 | 65 | 81   | 74 | 68 | 64 | 77   | 71 | 66 | 62 | 72   | 67 | 63 | 60 | 56  |  |   |   |  |   |
| 等価発光面積   |           |                 | cm <sup>2</sup> | 2.0           | 89   | 82 | 77 | 72 | 86   | 80 | 75 | 71 | 81   | 76 | 72 | 68 | 77   | 73 | 69 | 66 | 62  |  |   |   |  |   |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5             | 92            | 86   | 81 | 77 | 89 | 84   | 79 | 76 | 84 | 80   | 76 | 73 | 80 | 76   | 73 | 70 | 65 |     |  |   |   |  |   |
|          | 横方向 ( A ) |                 | 縦方向 ( B )       | 3.0           | 94   | 89 | 84 | 81 | 91   | 87 | 83 | 79 | 86   | 82 | 79 | 76 | 82   | 79 | 76 | 73 | 68  |  |   |   |  |   |
| 1.5m     | 1.9m      | 2.06m           | 4.0             | 97            | 92   | 89 | 86 | 94 | 90   | 87 | 84 | 89 | 86   | 83 | 81 | 84 | 82   | 80 | 77 | 72 |     |  |   |   |  |   |
| 2        | 2.52      | 2.6             | 5.0             | 98            | 95   | 92 | 89 | 96 | 92   | 90 | 87 | 91 | 88   | 86 | 84 | 86 | 84   | 82 | 80 | 75 |     |  |   |   |  |   |
| 2.5      | 3.14      | 3.17            | 7.0             | 100           | 98   | 95 | 93 | 98 | 95   | 93 | 91 | 93 | 91   | 89 | 87 | 88 | 86   | 85 | 83 | 78 |     |  |   |   |  |   |
| 3        | 3.75      | 3.75            | 10.0            | 102           | 100  | 98 | 96 | 99 | 97   | 96 | 94 | 94 | 93   | 91 | 90 | 89 | 88   | 87 | 86 | 80 |     |  |   |   |  |   |

