

屋内照明器具特性	
品番 (品名)	XF X430SLW
光源	LED4000_85_2840 ×1 2840.0 lm
管理番号	K0193785 (0) DB 1
BZ分類	BZ4

器具効率		100 % 上方光束 0 % 下方光束 100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z CM
保守率		良 中 否	0.6	59	47	39	34	57	46	39	34	55	45	38	34	53	44	38	34	32	
			0.8	69	58	50	44	67	57	50	44	65	55	49	44	62	54	48	44	42	
			1.0	75	65	58	52	74	64	57	52	71	63	56	51	68	61	56	51	49	
			1.25	81	72	65	59	79	71	64	59	76	69	63	59	74	67	62	58	56	
下方投影面積		cm ²	1.5	85	77	70	65	83	76	69	64	80	74	68	64	78	72	67	63	61	
			等価発光面積		cm ²	2.0	90	83	78	73	89	82	77	72	86	80	76	72	83	78	74
取付 高さ	器具間隔最大限		2.5	94		88	83	78	92	87	82	78	89	84	80	77	86	82	79	76	73
	横方向 (A) 縦方向 (B)		3.0	96	91	86	82	94	90	85	82	92	87	84	81	89	85	82	80	77	
1.5m	1.92 m	2.11 m	4.0	99	95	91	88	97	94	90	87	95	91	89	86	92	89	87	85	82	
2	2.54	2.66	5.0	101	97	94	91	99	96	93	91	97	94	91	89	94	92	90	88	85	
2.5	3.15	3.22	7.0	103	100	98	96	101	99	97	95	99	97	95	93	96	95	93	92	89	
3	3.77	3.8	10.0	104	103	101	99	103	101	100	98	101	99	98	97	98	97	96	95	92	

