

屋内照明器具特性	
品番 (品名)	XF X4 6 5 P HW
光源	LED4000_85_6020 ×1 6020.0 lm
管理番号	K0193346 (0) DB 1
B Z 分類	BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束				1 0 0 %																				
保守率		良 中 否	0 . 8 1	0 . 6	5 9	4 8	4 0	3 5	5 8	4 7	4 0	3 5	5 6	4 6	4 0	3 5	5 4	4 5	3 9	3 5	3 3			
			0 . 7 7	0 . 8	7 0	5 9	5 1	4 6	6 8	5 8	5 1	4 6	6 6	5 7	5 0	4 6	6 3	5 5	5 0	4 5	4 3			
			0 . 6 8	1 . 0	7 6	6 6	5 9	5 4	7 5	6 5	5 9	5 3	7 2	6 4	5 8	5 3	6 9	6 2	5 7	5 3	5 1			
				1 . 2 5	8 2	7 3	6 6	6 1	8 0	7 2	6 6	6 1	7 8	7 0	6 5	6 0	7 5	6 9	6 4	6 0	5 8			
下方投影面積		c m ²	1 . 5	8 6	7 8	7 2	6 7	8 4	7 7	7 1	6 6	8 2	7 5	7 0	6 6	7 9	7 3	6 9	6 5	6 3				
			等価発光面積	c m ²	2 . 0	9 1	8 5	7 9	7 5	9 0	8 4	7 9	7 4	8 7	8 2	7 7	7 3	8 4	8 0	7 6	7 3	7 0		
取付 高さ	器具間隔最大限		2 . 5	9 5	8 9	8 4	8 0	9 3	8 8	8 3	8 0	9 0	8 6	8 2	7 9	8 8	8 4	8 1	7 8	7 5				
	横方向 (A)	縦方向 (B)	3 . 0	9 7	9 2	8 8	8 4	9 5	9 1	8 7	8 4	9 3	8 9	8 5	8 2	9 0	8 7	8 4	8 1	7 9				
1 . 5 m	1 . 9 1 m	2 . 1 1 m	4 . 0	1 0 0	9 6	9 2	8 9	9 8	9 5	9 2	8 9	9 6	9 3	9 0	8 7	9 3	9 1	8 8	8 6	8 4				
2	2 . 5 2	2 . 6 6	5 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 5	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	8 9	8 7				
2 . 5	3 . 1 4	3 . 2 4	7 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 4	9 7	9 6	9 4	9 3	9 0				
3	3 . 7 5	3 . 8 2	1 0 . 0	1 0 5	1 0 3	1 0 2	1 0 0	1 0 4	1 0 2	1 0 1	9 9	1 0 1	1 0 0	9 9	9 7	9 9	9 8	9 7	9 6	9 3				

