

屋内照明器具特性	
品番 (品名)	X F X 4 6 0 R L N
光源	LED5000_85_6370 ×1 6370.0 lm
管理番号	K0193754 (0) DB 1
B Z 分類	B Z 4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束				1 0 0 %																			
保守率		良 中 否	0 . 8 1	0 . 6	5 9	4 7	4 0	3 4	5 8	4 7	3 9	3 4	5 5	4 6	3 9	3 4	5 3	4 5	3 9	3 4	3 2		
			0 . 7 7	0 . 8	6 9	5 8	5 1	4 5	6 8	5 7	5 0	4 5	6 5	5 6	5 0	4 5	6 3	5 5	4 9	4 5	4 3		
			0 . 6 8	1 . 0	7 6	6 6	5 8	5 3	7 4	6 5	5 8	5 3	7 1	6 3	5 7	5 2	6 9	6 2	5 6	5 2	5 0		
				1 . 2 5	8 2	7 2	6 6	6 0	8 0	7 2	6 5	6 0	7 7	7 0	6 4	6 0	7 4	6 8	6 3	5 9	5 7		
下方投影面積		c m ²	1 . 5	8 6	7 7	7 1	6 6	8 4	7 6	7 0	6 6	8 1	7 4	6 9	6 5	7 8	7 3	6 8	6 4	6 2			
等価発光面積			c m ²	2 . 0	9 1	8 4	7 9	7 4	8 9	8 3	7 8	7 3	8 6	8 1	7 7	7 3	8 4	7 9	7 5	7 2	7 0		
取付 高さ	器具間隔最大限		2 . 5	9 4	8 8	8 4	7 9	9 3	8 7	8 3	7 9	9 0	8 5	8 1	7 8	8 7	8 3	8 0	7 7	7 5			
	横方向 (A)		縦方向 (B)	3 . 0	9 7	9 1	8 7	8 3	9 5	9 0	8 6	8 3	9 2	8 8	8 5	8 2	9 0	8 6	8 3	8 1	7 8		
1 . 5m	1 . 9 3 m	2 . 1 1 m	4 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 3			
2	2 . 5 5	2 . 6 6	5 . 0	1 0 1	9 8	9 5	9 2	1 0 0	9 7	9 4	9 2	9 7	9 5	9 2	9 0	9 5	9 3	9 1	8 9	8 6			
2 . 5	3 . 1 8	3 . 2 3	7 . 0	1 0 3	1 0 1	9 9	9 6	1 0 2	1 0 0	9 8	9 6	9 9	9 7	9 6	9 4	9 7	9 5	9 4	9 2	9 0			
3	3 . 8	3 . 8	1 0 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 8	9 7	9 9	9 7	9 6	9 5	9 3			

