

屋内照明器具特性	
品番 (品名)	X F X 4 6 9 K P N
光源	LED5000_85_6580 ×1 6580.0 lm
管理番号	K0192151 (0) D 1
B Z 分類	BZ5 / 2.8 / BZ4

器具効率		1 0 0 % 上方光束 1 % 下方光束 9 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
			室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 0 . 8 1 中 0 . 7 7 否 0 . 6 8	0 . 6	5 7	4 5	3 7	3 2	5 6	4 4	3 7	3 2	5 3	4 3	3 6	3 1	5 1	4 2	3 6	3 1	2 9	
			0 . 8	6 7	5 6	4 8	4 2	6 6	5 5	4 7	4 2	6 3	5 3	4 7	4 2	6 0	5 2	4 6	4 1	3 9	
			1 . 0	7 4	6 3	5 5	5 0	7 2	6 2	5 5	5 0	6 9	6 1	5 4	4 9	6 6	5 9	5 3	4 9	4 6	
			1 . 2 5	8 0	7 0	6 3	5 7	7 8	6 9	6 2	5 7	7 5	6 7	6 1	5 7	7 2	6 6	6 0	5 6	5 4	
下方投影面積 等価発光面積		c m ²	1 . 5	8 4	7 5	6 8	6 3	8 2	7 4	6 8	6 3	7 9	7 2	6 7	6 2	7 6	7 0	6 5	6 1	5 9	
			2 . 0	9 0	8 2	7 6	7 2	8 8	8 1	7 6	7 1	8 5	7 9	7 4	7 0	8 2	7 7	7 3	6 9	6 7	
取付 高さ	器具間隔最大限		2 . 5	9 3	8 7	8 2	7 7	9 1	8 6	8 1	7 7	8 8	8 4	7 9	7 6	8 6	8 1	7 8	7 5	7 2	
	横方向 (A)	縦方向 (B)	3 . 0	9 6	9 0	8 6	8 2	9 4	8 9	8 5	8 1	9 1	8 7	8 3	8 0	8 8	8 5	8 2	7 9	7 6	
1 . 5m	1 . 9 4 m	2 . 1 1 m	4 . 0	9 9	9 5	9 1	8 7	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 5	9 2	8 9	8 6	8 4	8 1	
2	2 . 5 6	2 . 6 6	5 . 0	1 0 1	9 7	9 4	9 1	9 9	9 6	9 3	9 0	9 6	9 4	9 1	8 9	9 4	9 1	8 9	8 7	8 4	
2 . 5	3 . 1 8	3 . 2 2	7 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 6	9 4	9 3	9 1	8 8	
3	3 . 8	3 . 8 1	1 0 . 0	1 0 4	1 0 3	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 0	9 9	9 8	9 6	9 8	9 7	9 5	9 4	9 1	

