

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | XF X4 4 9 R P N              |
| 光源       | LED5000_85_3770 ×1 3770.0 lm |
| 管理番号     | K0192152 ( 0 ) D 1           |
| B Z 分類   | BZ5                          |

| 器具効率   |  |           | 100 %           |           | 反射率             | 天井  | 80 %                |     |    |     | 70 % |     |    |     | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|--------|--|-----------|-----------------|-----------|-----------------|-----|---------------------|-----|----|-----|------|-----|----|-----|------|----|----|----|------|----|----|----|-----|
|        |  |           |                 |           |                 | 壁   | 70                  | 50  | 30 | 10  | 70   | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|        |  |           |                 |           |                 | 床   | 10 %                |     |    |     | 10 % |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|        |  |           |                 |           |                 | 室指数 | 照明率 ( X0.01 ) Z C M |     |    |     |      |     |    |     |      |    |    |    |      |    |    |    |     |
| 保守率    |  |           | 良<br>中<br>否     | 0.81      | 0.6             | 57  | 45                  | 37  | 31 | 55  | 44   | 36  | 31 | 53  | 43   | 36 | 31 | 51 | 42   | 36 | 31 | 29 |     |
|        |  |           |                 | 0.77      | 0.8             | 67  | 55                  | 47  | 42 | 65  | 55   | 47  | 42 | 63  | 53   | 46 | 41 | 60 | 52   | 46 | 41 | 39 |     |
|        |  |           |                 | 0.68      | 1.0             | 73  | 63                  | 55  | 49 | 72  | 62   | 55  | 49 | 69  | 60   | 54 | 49 | 66 | 59   | 53 | 48 | 46 |     |
|        |  |           |                 |           | 1.25            | 79  | 70                  | 62  | 57 | 78  | 69   | 62  | 57 | 75  | 67   | 61 | 56 | 72 | 65   | 60 | 56 | 53 |     |
| 下方投影面積 |  |           | cm <sup>2</sup> | 1.5       | 84              | 75  | 68                  | 62  | 82 | 74  | 67   | 62  | 79 | 72  | 66   | 62 | 76 | 70 | 65   | 61 | 59 |    |     |
|        |  |           |                 | 等価発光面積    | cm <sup>2</sup> | 2.0 | 89                  | 82  | 76 | 71  | 88   | 81  | 75 | 71  | 85   | 79 | 74 | 70 | 82   | 77 | 73 | 69 | 67  |
| 取付高さ   |  | 器具間隔最大限   |                 |           | 2.5             | 93  | 87                  | 81  | 77 | 91  | 86   | 81  | 76 | 88  | 83   | 79 | 75 | 86 | 81   | 78 | 74 | 72 |     |
|        |  | 横方向 ( A ) |                 | 縦方向 ( B ) | 3.0             | 95  | 90                  | 85  | 81 | 94  | 89   | 84  | 81 | 91  | 87   | 83 | 80 | 88 | 85   | 81 | 78 | 76 |     |
| 1.5m   |  | 1.99 m    |                 | 2.12 m    | 4.0             | 99  | 94                  | 90  | 87 | 97  | 93   | 90  | 86 | 94  | 91   | 88 | 85 | 92 | 89   | 86 | 84 | 81 |     |
| 2      |  | 2.62      |                 | 2.66      | 5.0             | 101 | 97                  | 94  | 91 | 99  | 96   | 93  | 90 | 96  | 94   | 91 | 89 | 94 | 91   | 89 | 87 | 85 |     |
| 2.5    |  | 3.26      |                 | 3.22      | 7.0             | 103 | 100                 | 98  | 95 | 101 | 99   | 97  | 95 | 99  | 97   | 95 | 93 | 96 | 95   | 93 | 91 | 89 |     |
| 3      |  | 3.89      |                 | 3.8       | 10.0            | 104 | 103                 | 101 | 99 | 103 | 101  | 100 | 98 | 101 | 99   | 98 | 96 | 98 | 97   | 96 | 95 | 92 |     |

