

屋内照明器具特性	
品番 (品名)	NNLK42742 + NEL4300EX
光源	LED5000_85_3110 ×1 3110.0 lm
管理番号	K0192145 (0) D 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.81	0.6	56	44	36	30	55	43	35	30	52	42	35	30	50	41	34	30	28
			0.77	0.8	66	54	46	40	64	53	46	40	61	52	45	40	59	50	44	39	37
			0.68	1.0	72	61	53	47	71	60	53	47	68	59	52	47	65	57	51	46	44
				1.25	78	68	60	55	77	67	60	54	73	65	59	54	70	64	58	53	51
下方投影面積		cm ²		1.5	82	73	66	60	81	72	65	60	77	70	64	59	74	68	63	59	56
			等価発光面積	cm ²	2.0	88	80	74	68	86	79	73	68	83	77	72	67	80	75	70	66
取付 高さ	器具間隔最大限		2.5	92	85	79	74	90	84	78	74	87	81	77	73	84	79	75	72	69	
	横方向 (A)	縦方向 (B)	3.0	94	88	83	78	92	87	82	78	89	85	80	77	86	82	79	76	73	
1.5m	1.96 m	2.1 m	4.0	97	92	88	84	96	91	87	84	93	89	85	82	90	87	84	81	78	
2	2.58	2.64	5.0	99	95	91	88	98	94	90	87	95	92	89	86	92	89	87	85	82	
2.5	3.21	3.2	7.0	102	98	96	93	100	97	95	92	97	95	93	90	95	93	91	89	86	
3	3.84	3.78	10.0	103	101	99	97	102	100	98	96	99	98	96	94	97	95	94	92	89	

