

屋内照明器具特性	
品番 (品名)	F Y Y 5 6 0 2 1 C
光源	LED5000_85_3990 ×1 3990.0 l m
管理番号	K0129474 (2) DB 1
B Z 分類	BZ3 / 0.9 / BZ2 / 4.5 / BZ3 / 6.0 / BZ2

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		4 1 %	室指数	照明率 (X 0 . 0 1) Z C M																	
下方光束		5 9 %																			
保守率		良 中 否	0 . 7 7	0 . 6	5 6	4 6	3 9	3 4	5 3	4 3	3 7	3 3	4 7	3 9	3 4	3 1	4 1	3 5	3 1	2 9	2 4
			0 . 7 2	0 . 8	6 5	5 6	4 9	4 4	6 1	5 3	4 7	4 3	5 4	4 8	4 3	4 0	4 8	4 3	3 9	3 6	3 1
			0 . 6 8	1 . 0	7 1	6 3	5 6	5 2	6 7	5 9	5 4	5 0	5 9	5 3	4 9	4 6	5 2	4 8	4 4	4 2	3 5
			1 . 2 5	7 6	6 9	6 3	5 8	7 2	6 5	6 0	5 6	6 4	5 9	5 5	5 1	5 6	5 2	4 9	4 7	3 9	
下方投影面積		c m ²	1 . 5	8 0	7 3	6 8	6 3	7 5	6 9	6 4	6 1	6 7	6 2	5 8	5 5	5 9	5 5	5 2	5 0	4 2	
			等価発光面積		c m ²	2 . 0	8 5	7 9	7 4	7 0	8 0	7 5	7 1	6 7	7 1	6 7	6 4	6 1	6 2	5 9	5 7
取付高さ	器具間隔最大限		2 . 5	8 7	8 3	7 9	7 5	8 2	7 8	7 5	7 2	7 3	7 0	6 7	6 5	6 4	6 2	6 0	5 8	4 8	
	横方向 (A) 縦方向 (B)		3 . 0	8 9	8 5	8 2	7 8	8 4	8 1	7 7	7 5	7 5	7 2	6 9	6 7	6 5	6 4	6 2	6 0	5 0	
1 . 5 m	1 . 8 4 m	1 . 8 1 m	4 . 0	9 2	8 9	8 6	8 3	8 7	8 4	8 1	7 9	7 7	7 5	7 3	7 1	6 7	6 6	6 4	6 3	5 2	
2	2 . 4 4	2 . 2 5	5 . 0	9 3	9 1	8 8	8 6	8 8	8 6	8 4	8 2	7 8	7 6	7 5	7 3	6 8	6 7	6 6	6 5	5 3	
2 . 5	3 . 0 3	2 . 7 1	7 . 0	9 5	9 3	9 1	8 9	9 0	8 8	8 6	8 5	7 9	7 8	7 7	7 6	7 0	6 9	6 8	6 7	5 4	
3	3 . 6 2	3 . 2	1 0 . 0	9 6	9 5	9 3	9 2	9 1	9 0	8 8	8 7	8 1	8 0	7 9	7 8	7 1	7 0	6 9	6 9	5 6	

