

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | F Y Y 5 6 0 2 1 K            |
| 光源       | LED5000_85_5210 ×1 5210.0 lm |
| 管理番号     | K0176833 ( 1 ) DB 1          |
| B Z 分類   | BZ3 / 0.7 / BZ2              |

| 器具効率     |                     | 100 %           | 反射率    | 天井              | 80 %                |      |    |    | 70 % |      |    |    | 50 % |      |    |    | 30 % |      |    |    | 0 % |     |
|----------|---------------------|-----------------|--------|-----------------|---------------------|------|----|----|------|------|----|----|------|------|----|----|------|------|----|----|-----|-----|
|          |                     |                 |        | 壁               | 70                  | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 70   | 50   | 30 | 10 | 0 % |     |
|          |                     |                 |        |                 | 床                   | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |      | 10 % |    |    |     | 0 % |
|          |                     |                 |        |                 | 照明率 ( X0.01 ) Z C M |      |    |    |      |      |    |    |      |      |    |    |      |      |    |    |     |     |
| 保守率      |                     | 良<br>中<br>否     | 0.77   | 0.6             | 55                  | 45   | 39 | 34 | 52   | 43   | 37 | 33 | 45   | 38   | 34 | 30 | 39   | 34   | 30 | 28 | 23  |     |
|          |                     |                 | 0.72   | 0.8             | 64                  | 55   | 49 | 44 | 60   | 52   | 46 | 42 | 53   | 46   | 42 | 38 | 46   | 41   | 38 | 35 | 29  |     |
|          |                     |                 | 0.68   | 1.0             | 71                  | 62   | 56 | 51 | 66   | 58   | 53 | 49 | 58   | 52   | 48 | 44 | 50   | 46   | 43 | 40 | 33  |     |
|          |                     |                 |        | 1.25            | 76                  | 68   | 62 | 58 | 71   | 64   | 59 | 55 | 62   | 57   | 53 | 50 | 54   | 50   | 47 | 45 | 37  |     |
| 下方投影面積   |                     | cm <sup>2</sup> | 1.5    | 79              | 72                  | 67   | 62 | 74 | 68   | 63   | 60 | 65 | 60   | 57   | 54 | 56 | 53   | 50   | 48 | 39 |     |     |
|          |                     |                 | 等価発光面積 | cm <sup>2</sup> | 2.0                 | 84   | 78 | 73 | 69   | 79   | 74 | 69 | 66   | 69   | 65 | 62 | 59   | 59   | 57 | 55 | 53  | 43  |
| 取付<br>高さ | 器具間隔最大限             |                 | 2.5    | 87              | 82                  | 78   | 74 | 81 | 77   | 73   | 70 | 71 | 68   | 65   | 63 | 61 | 59   | 57   | 56 | 45 |     |     |
|          | 横方向 ( A ) 縦方向 ( B ) |                 | 3.0    | 89              | 84                  | 81   | 78 | 83 | 79   | 76   | 73 | 73 | 70   | 68   | 66 | 63 | 61   | 59   | 58 | 46 |     |     |
| 1.5m     | 1.82 m              | 1.76 m          | 4.0    | 91              | 88                  | 85   | 82 | 85 | 83   | 80   | 78 | 75 | 73   | 71   | 69 | 65 | 63   | 62   | 61 | 48 |     |     |
| 2        | 2.41                | 2.19            | 5.0    | 92              | 90                  | 87   | 85 | 87 | 84   | 82   | 80 | 76 | 74   | 73   | 71 | 66 | 64   | 63   | 62 | 49 |     |     |
| 2.5      | 2.99                | 2.64            | 7.0    | 94              | 92                  | 90   | 89 | 88 | 87   | 85   | 84 | 77 | 76   | 75   | 74 | 67 | 66   | 65   | 64 | 51 |     |     |
| 3        | 3.58                | 3.1             | 10.0   | 95              | 94                  | 93   | 91 | 90 | 88   | 87   | 86 | 78 | 77   | 77   | 76 | 68 | 67   | 67   | 66 | 52 |     |     |

