

屋内照明器具特性	
品番 (品名)	F Y Y 5 6 0 2 2 K
光源	LED5000_85_5210 ×1 5210.0 lm
管理番号	K0176833 (1) DB 1
BZ分類	BZ3 / 0.7 / BZ2

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.77	0.6	55	45	39	34	52	43	37	33	45	38	34	30	39	34	30	28	23				
			0.72	0.8	64	55	49	44	60	52	46	42	53	46	42	38	46	41	38	35	29				
			0.68	1.0	71	62	56	51	66	58	53	49	58	52	48	44	50	46	43	40	33				
				1.25	76	68	62	58	71	64	59	55	62	57	53	50	54	50	47	45	37				
下方投影面積		cm ²		1.5	79	72	67	62	74	68	63	60	65	60	57	54	56	53	50	48	39				
			等価発光面積	cm ²	2.0	84	78	73	69	79	74	69	66	69	65	62	59	59	57	55	53	43			
取付高さ	器具間隔最大限			2.5	87	82	78	74	81	77	73	70	71	68	65	63	61	59	57	56	45				
	横方向 (A) 縦方向 (B)			3.0	89	84	81	78	83	79	76	73	73	70	68	66	63	61	59	58	46				
1.5m	1.82 m	1.76 m		4.0	91	88	85	82	85	83	80	78	75	73	71	69	65	63	62	61	48				
2	2.41	2.19		5.0	92	90	87	85	87	84	82	80	76	74	73	71	66	64	63	62	49				
2.5	2.99	2.64		7.0	94	92	90	89	88	87	85	84	77	76	75	74	67	66	65	64	51				
3	3.58	3.1		10.0	95	94	93	91	90	88	87	86	78	77	77	76	68	67	67	66	52				

