

| 屋内照明器具特性 |                                         |
|----------|-----------------------------------------|
| 品番 (品名)  | F Y Y 5 6 0 2 3 C                       |
| 光源       | LED5000_85_3990 ×1 3990.0 lm            |
| 管理番号     | K0129474 ( 2 ) DB 1                     |
| B Z 分類   | BZ3 / 0.9 / BZ2 / 4.5 / BZ3 / 6.0 / BZ2 |

| 器具効率             |                     | 100 %                              | 反射率  | 天井                 | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|------------------|---------------------|------------------------------------|------|--------------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|                  |                     |                                    |      | 壁                  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|                  |                     |                                    |      | 床                  | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
| 上方光束<br>下方光束     |                     | 41 %<br>59 %                       | 室指数  | 照明率 ( X0.01 ) Z CM |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率              |                     | 良<br>中<br>否                        | 0.77 | 0.6                | 56   | 46 | 39 | 34 | 53   | 43 | 37 | 33 | 47   | 39 | 34 | 31 | 41   | 35 | 31 | 29 | 24  |
|                  |                     |                                    | 0.72 | 0.8                | 65   | 56 | 49 | 44 | 61   | 53 | 47 | 43 | 54   | 48 | 43 | 40 | 48   | 43 | 39 | 36 | 31  |
|                  |                     |                                    | 0.68 | 1.0                | 71   | 63 | 56 | 52 | 67   | 59 | 54 | 50 | 59   | 53 | 49 | 46 | 52   | 48 | 44 | 42 | 35  |
|                  |                     |                                    | 1.25 | 76                 | 69   | 63 | 58 | 72 | 65   | 60 | 56 | 64 | 59   | 55 | 51 | 56 | 52   | 49 | 47 | 39 |     |
| 下方投影面積<br>等価発光面積 |                     | cm <sup>2</sup><br>cm <sup>2</sup> | 1.5  | 80                 | 73   | 68 | 63 | 75 | 69   | 64 | 61 | 67 | 62   | 58 | 55 | 59 | 55   | 52 | 50 | 42 |     |
|                  |                     |                                    | 2.0  | 85                 | 79   | 74 | 70 | 80 | 75   | 71 | 67 | 71 | 67   | 64 | 61 | 62 | 59   | 57 | 55 | 46 |     |
| 取付<br>高さ         | 器具間隔最大限             |                                    | 2.5  | 87                 | 83   | 79 | 75 | 82 | 78   | 75 | 72 | 73 | 70   | 67 | 65 | 64 | 62   | 60 | 58 | 48 |     |
|                  | 横方向 ( A ) 縦方向 ( B ) |                                    | 3.0  | 89                 | 85   | 82 | 78 | 84 | 81   | 77 | 75 | 75 | 72   | 69 | 67 | 65 | 64   | 62 | 60 | 50 |     |
| 1.5m             | 1.84 m              | 1.81 m                             | 4.0  | 92                 | 89   | 86 | 83 | 87 | 84   | 81 | 79 | 77 | 75   | 73 | 71 | 67 | 66   | 64 | 63 | 52 |     |
| 2                | 2.44                | 2.25                               | 5.0  | 93                 | 91   | 88 | 86 | 88 | 86   | 84 | 82 | 78 | 76   | 75 | 73 | 68 | 67   | 66 | 65 | 53 |     |
| 2.5              | 3.03                | 2.71                               | 7.0  | 95                 | 93   | 91 | 89 | 90 | 88   | 86 | 85 | 79 | 78   | 77 | 76 | 70 | 69   | 68 | 67 | 54 |     |
| 3                | 3.62                | 3.2                                | 10.0 | 96                 | 95   | 93 | 92 | 91 | 90   | 88 | 87 | 81 | 80   | 79 | 78 | 71 | 70   | 69 | 69 | 56 |     |

