

屋内照明器具特性	
品番 (品名)	F Y Y 5 6 0 2 3 J
光源	F Y Y 5 6 0 2 3 J × 1 3 9 9 0 . 0 l m
管理番号	K 0 1 2 9 4 7 4 (2) D B 1
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		4 1 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		5 9 %																				
保守率		良 中 否	0 . 7 7	0 . 6	5 6	4 6	3 9	3 4	5 3	4 3	3 7	3 3	4 7	3 9	3 4	3 1	4 1	3 5	3 1	2 9	2 4	
			0 . 7 2	0 . 8	6 5	5 6	4 9	4 4	6 1	5 3	4 7	4 3	5 4	4 8	4 3	4 0	4 8	4 3	3 9	3 6	3 1	
			0 . 6 8	1 . 0	7 1	6 3	5 6	5 2	6 7	5 9	5 4	5 0	5 9	5 3	4 9	4 6	5 2	4 8	4 4	4 2	3 5	
				1 . 2 5	7 6	6 9	6 3	5 8	7 2	6 5	6 0	5 6	6 4	5 9	5 5	5 1	5 6	5 2	4 9	4 7	3 9	
下方投影面積		c m ²	1 . 5	8 0	7 3	6 8	6 3	7 5	6 9	6 4	6 1	6 7	6 2	5 8	5 5	5 9	5 5	5 2	5 0	4 2		
等価発光面積		c m ²	2 . 0	8 5	7 9	7 4	7 0	8 0	7 5	7 1	6 7	7 1	6 7	6 4	6 1	6 2	5 9	5 7	5 5	4 6		
取付 高さ	器具間隔最大限		2 . 5	8 7	8 3	7 9	7 5	8 2	7 8	7 5	7 2	7 3	7 0	6 7	6 5	6 4	6 2	6 0	5 8	4 8		
	横方向 (A)		縦方向 (B)	3 . 0	8 9	8 5	8 2	7 8	8 4	8 1	7 7	7 5	7 5	7 2	6 9	6 7	6 5	6 4	6 2	6 0	5 0	
1 . 5 m	1 . 8 4 m	1 . 8 1 m	4 . 0	9 2	8 9	8 6	8 3	8 7	8 4	8 1	7 9	7 7	7 5	7 3	7 1	6 7	6 6	6 4	6 3	5 2		
2	2 . 4 4	2 . 2 5	5 . 0	9 3	9 1	8 8	8 6	8 8	8 6	8 4	8 2	7 8	7 6	7 5	7 3	6 8	6 7	6 6	6 5	5 3		
2 . 5	3 . 0 3	2 . 7 1	7 . 0	9 5	9 3	9 1	8 9	9 0	8 8	8 6	8 5	7 9	7 8	7 7	7 6	7 0	6 9	6 8	6 7	5 4		
3	3 . 6 2	3 . 2	1 0 . 0	9 6	9 5	9 3	9 2	9 1	9 0	8 8	8 7	8 1	8 0	7 9	7 8	7 1	7 0	6 9	6 9	5 6		

