

屋内照明器具特性	
品番 (品名)	F Y Y 5 6 0 2 6 C
光源	LED4000_85_3670 ×1 3670.0 lm
管理番号	K0129474 (2) DB 1
B Z 分類	BZ3 / 0.9 / BZ2 / 4.5 / BZ3 / 6.0 / BZ2

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		41 %	室指数	照明率 (X0.01)																			Z C M	
下方光束		59 %																						
保守率		良 中 否	0.77	0.6	56	46	39	34	53	43	37	33	47	39	34	31	41	35	31	29	24			
			0.72	0.8	65	56	49	44	61	53	47	43	54	48	43	40	48	43	39	36	31			
			0.68	1.0	71	63	56	52	67	59	54	50	59	53	49	46	52	48	44	42	35			
				1.25	76	69	63	58	72	65	60	56	64	59	55	51	56	52	49	47	39			
下方投影面積		c m ²	1.5	80	73	68	63	75	69	64	61	67	62	58	55	59	55	52	50	42				
等価発光面積			c m ²	2.0	85	79	74	70	80	75	71	67	71	67	64	61	62	59	57	55	46			
取付 高さ	器具間隔最大限		2.5	87	83	79	75	82	78	75	72	73	70	67	65	64	62	60	58	48				
	横方向 (A) 縦方向 (B)		3.0	89	85	82	78	84	81	77	75	75	72	69	67	65	64	62	60	50				
1.5m	1.84 m	1.81 m	4.0	92	89	86	83	87	84	81	79	77	75	73	71	67	66	64	63	52				
2	2.44	2.25	5.0	93	91	88	86	88	86	84	82	78	76	75	73	68	67	66	65	53				
2.5	3.03	2.71	7.0	95	93	91	89	90	88	86	85	79	78	77	76	70	69	68	67	54				
3	3.62	3.2	10.0	96	95	93	92	91	90	88	87	81	80	79	78	71	70	69	69	56				

