

屋内照明器具特性	
品番 (品名)	HH- CD0 8 1 5 DJ
光源	LED6500_70_4000 ×1 4000.0 lm
管理番号	K0155163 (0) DB 1
BZ分類	BZ5

器具効率		100 % 上方光束 8 % 下方光束 92 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	55	43	35	30	54	42	35	30	50	40	34	29	48	39	33	28	26	
			0.6	0.8	65	53	45	40	63	52	45	39	59	50	44	39	56	48	42	38	35	
			0.56	1.0	71	61	53	47	69	59	52	46	65	57	50	45	62	54	49	44	41	
				1.25	77	67	60	54	75	66	59	53	71	63	57	52	67	61	55	51	48	
下方投影面積 等価発光面積		cm ² cm ²		1.5	81	72	65	60	79	71	64	59	75	68	62	57	71	65	60	56	52	
			2.0	87	79	73	68	85	77	72	67	80	74	69	65	76	71	67	63	59		
取付 高さ	器具間隔最大限			2.5	90	84	78	73	88	82	77	72	84	79	74	70	80	75	72	68	64	
	横方向 (A)		縦方向 (B)	3.0	93	87	82	78	90	85	80	76	86	82	78	74	82	78	75	72	68	
H m	1.23 H m	1.23 H m	4.0	96	91	87	83	94	89	85	82	89	86	82	80	85	82	80	77	73		
			5.0	98	94	90	87	96	92	89	86	91	88	86	83	87	85	83	80	76		
			7.0	100	97	94	92	98	95	93	90	94	92	89	87	90	88	86	84	80		
			10.0	102	100	98	96	100	98	96	94	96	94	92	91	92	90	89	88	83		

