

屋内照明器具特性	
品番 (品名)	HH- CD0820AZ
光源	LED6200_70_4299 ×1 4299.0 lm
管理番号	K0155145 (0) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		8 %	室指数	照明率 (X0.01)																			ZCM	
下方光束		92 %																						
保守率		良 中 否	0.63	0.6	55	43	35	29	53	42	34	29	50	40	33	28	47	38	32	28	25			
			0.6	0.8	64	53	45	39	62	52	44	39	59	50	43	38	55	48	42	37	34			
			0.56	1.0	71	60	52	46	69	59	51	46	65	56	50	45	61	54	48	44	41			
				1.25	77	67	59	53	74	65	58	53	70	63	56	52	66	60	55	50	47			
下方投影面積		cm ²	1.5	81	72	65	59	78	70	63	58	74	67	61	57	70	64	59	55	52				
等価発光面積		cm ²	2.0	86	79	72	67	84	77	71	66	80	74	69	64	75	71	66	63	59				
取付 高さ	器具間隔最大限		2.5	90	83	77	73	87	81	76	72	83	78	73	70	79	75	71	68	64				
	横方向 (A)	縦方向 (B)	3.0	92	86	81	77	90	85	80	76	86	81	77	74	81	78	74	71	67				
H _m	1.24 H _m	1.24 H _m	4.0	95	91	86	83	93	89	85	81	89	85	82	79	85	82	79	76	72				
			5.0	97	93	90	86	95	91	88	85	91	88	85	82	87	84	82	80	75				
			7.0	100	97	94	91	97	95	92	90	93	91	89	87	89	87	86	84	79				
			10.0	101	99	97	95	99	97	95	93	95	93	92	90	91	90	88	87	82				

