

屋内照明器具特性	
品番 (品名)	HH- CD0834A
光源	LED6200_70_4299 ×1 4299.0 lm
管理番号	K0161951 (0) D 1
BZ分類	BZ6 / 0.9 / BZ5

器具効率		1 0 0 % 上方光束 6 % 下方光束 9 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
				室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 3	0 . 6	0 . 5 6	0 . 6	5 3	4 0	3 2	2 6	5 1	3 9	3 1	2 6	4 8	3 8	3 0	2 5	4 5	3 6	3 0	2 5	2 3
			0 . 6	0 . 8	6 3	5 1	4 2	3 6	6 1	4 9	4 2	3 6	5 7	4 7	4 0	3 5	5 4	4 6	3 9	3 4	3 2		
			1 . 0	6 9	5 8	5 0	4 3	6 7	5 7	4 9	4 3	6 4	5 4	4 7	4 2	6 0	5 2	4 6	4 1	3 8			
			1 . 2 5	7 6	6 5	5 7	5 1	7 3	6 4	5 6	5 0	6 9	6 1	5 4	4 9	6 6	5 9	5 3	4 8	4 5			
下方投影面積		c m ²	1 . 5	8 0	7 0	6 3	5 7	7 8	6 9	6 2	5 6	7 3	6 6	6 0	5 5	7 0	6 3	5 8	5 3	5 0			
			等価発光面積		c m ²	2 . 0	8 6	7 7	7 1	6 5	8 3	7 6	7 0	6 4	7 9	7 3	6 7	6 3	7 5	7 0	6 5	6 1	5 8
取付	器具間隔最大限					2 . 5	8 9	8 2	7 6	7 1	8 7	8 1	7 5	7 0	8 3	7 7	7 3	6 8	7 9	7 4	7 0	6 7	6 3
高さ	横方向 (A)			縦方向 (B)		3 . 0	9 2	8 6	8 0	7 6	9 0	8 4	7 9	7 5	8 6	8 1	7 6	7 3	8 2	7 8	7 4	7 1	6 7
H m	1 . 4 7 H m			1 . 4 7 H m		4 . 0	9 5	9 0	8 6	8 2	9 3	8 9	8 4	8 1	8 9	8 5	8 2	7 8	8 5	8 2	7 9	7 6	7 2
						5 . 0	9 8	9 3	8 9	8 6	9 5	9 1	8 8	8 5	9 1	8 8	8 5	8 2	8 7	8 5	8 2	8 0	7 6
						7 . 0	1 0 0	9 7	9 4	9 1	9 8	9 5	9 2	9 0	9 4	9 1	8 9	8 7	9 0	8 8	8 6	8 4	8 0
						1 0 . 0	1 0 2	1 0 0	9 7	9 5	1 0 0	9 8	9 6	9 4	9 6	9 4	9 2	9 1	9 2	9 1	8 9	8 8	8 3

