

屋内照明器具特性	
品番 (品名)	HH- CD0838A
光源	LED6200_70_4100 ×1 4100.0 lm
管理番号	K0161979 (0) D 1
BZ分類	BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	5 5	4 3	3 5	2 9	5 4	4 2	3 4	2 9	5 1	4 1	3 4	2 9	4 9	4 0	3 3	2 9	2 6
			0 . 6	0 . 8	6 5	5 3	4 5	3 9	6 4	5 3	4 5	3 9	6 1	5 1	4 4	3 9	5 8	4 9	4 3	3 8	3 6
			0 . 5 6	1 . 0	7 2	6 1	5 3	4 7	7 0	6 0	5 2	4 7	6 7	5 8	5 1	4 6	6 4	5 6	5 0	4 6	4 3
				1 . 2 5	7 8	6 8	6 0	5 4	7 6	6 7	6 0	5 4	7 3	6 5	5 8	5 3	7 0	6 3	5 7	5 3	5 0
下方投影面積 等価発光面積		c m ²		1 . 5	8 2	7 3	6 6	6 0	8 0	7 2	6 5	6 0	7 7	7 0	6 4	5 9	7 4	6 7	6 2	5 8	5 5
				2 . 0	8 8	8 0	7 4	6 8	8 6	7 9	7 3	6 8	8 3	7 6	7 1	6 7	7 9	7 4	7 0	6 6	6 3
				2 . 5	9 1	8 5	7 9	7 4	9 0	8 3	7 8	7 4	8 6	8 1	7 6	7 2	8 3	7 9	7 5	7 1	6 8
				3 . 0	9 4	8 8	8 3	7 9	9 2	8 7	8 2	7 8	8 9	8 4	8 0	7 7	8 6	8 2	7 8	7 5	7 2
H m	1 . 3 4 H m	1 . 3 4 H m		4 . 0	9 7	9 3	8 8	8 5	9 6	9 1	8 7	8 4	9 2	8 9	8 5	8 2	8 9	8 6	8 3	8 1	7 8
				5 . 0	9 9	9 5	9 2	8 8	9 8	9 4	9 1	8 8	9 4	9 1	8 8	8 6	9 1	8 9	8 6	8 4	8 1
				7 . 0	1 0 2	9 9	9 6	9 3	1 0 0	9 7	9 5	9 2	9 7	9 5	9 2	9 0	9 4	9 2	9 0	8 8	8 5
				1 0 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	9 9	9 7	9 6	9 4	9 6	9 5	9 3	9 2	8 9

