

屋内照明器具特性	
品番 (品名)	HH- CD0843AS
光源	LED6200_70_4299 ×1 4299.0 lm
管理番号	K0161883 (0) D 1
BZ分類	BZ6/0.7/BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		6 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		94 %																								
保守率		良 中 否	0.63	0.6	53	41	33	27	52	40	32	27	49	38	31	26	46	37	31	26	23					
			0.6	0.8	63	51	43	37	61	50	42	37	58	48	41	36	55	46	40	35	33					
			0.56	1.0	70	59	50	44	68	57	50	44	64	55	48	43	60	53	47	42	39					
				1.25	76	66	58	52	74	64	57	51	70	62	55	50	66	59	53	49	46					
下方投影面積		cm ²	1.5	80	71	63	57	78	69	62	57	74	66	60	55	70	64	58	54	51						
等価発光面積			cm ²	2.0	86	78	71	66	84	76	70	65	79	73	68	63	76	70	66	62	58					
取付 高さ	器具間隔最大限		2.5	90	83	77	71	87	81	75	71	83	78	73	69	79	75	71	67	63						
	横方向 (A)		縦方向 (B)		3.0	92	86	81	76	90	84	79	75	86	81	77	73	82	78	74	71	67				
H m	1.40 H m	1.39 H m	4.0	96	90	86	82	93	89	85	81	89	85	82	79	85	82	79	76	72						
			5.0	98	93	90	86	95	92	88	85	91	88	85	82	88	85	82	80	76						
			7.0	100	97	94	91	98	95	92	90	94	92	89	87	90	88	86	84	80						
			10.0	102	100	97	95	100	98	96	94	96	94	92	91	92	91	89	88	83						

