

屋内照明器具特性	
品番 (品名)	HH- CD0857A
光源	LED6200_70_4000 ×1 4000.0 lm
管理番号	K0157936 (0) DB 1
BZ分類	BZ5

器具効率		100 % 上方光束 5 % 下方光束 95 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	55	42	34	29	53	41	34	28	50	40	33	28	48	39	32	28	25	
			0.6	0.8	64	53	44	38	63	52	44	38	59	50	43	38	56	48	42	37	34	
				1.0	71	60	52	46	69	59	51	45	65	56	50	45	62	54	49	44	41	
			0.56	1.25	77	67	59	53	75	65	58	52	71	63	57	52	67	61	55	51	48	
下方投影面積		cm ²		1.5	81	72	64	58	79	70	63	58	75	68	62	57	71	65	60	56	53	
			等価発光面積	cm ²	2.0	87	79	72	67	85	77	71	66	81	74	69	65	77	72	67	63	60
取付高さ	器具間隔最大限			2.5	90	83	78	73	88	82	76	72	84	79	74	70	80	76	72	69	65	
	横方向 (A)		縦方向 (B)	3.0	93	87	81	77	91	85	80	76	87	82	78	74	83	79	76	73	69	
1.5m	1.96 m	1.96 m	4.0	96	91	87	83	94	90	85	82	90	86	83	80	87	83	81	78	74		
2	2.6	2.6	5.0	98	94	90	87	96	92	89	86	92	89	86	83	89	86	84	81	77		
2.5	3.17	3.18	7.0	101	97	94	92	99	96	93	90	95	92	90	88	91	89	87	86	82		
3	3.81	3.81	10.0	102	100	98	96	100	98	96	94	97	95	93	92	93	92	91	89	85		

