

屋内照明器具特性	
品番 (品名)	HH- CD0 8 9 2 A
光源	LED6200_70_4299 ×1 4299.0 lm
管理番号	K0161510 (0) D 1
BZ分類	BZ6 / 0.7 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		2 3 % 7 7 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 3	0 . 6	5 1	3 9	3 1	2 6	4 9	3 8	3 0	2 5	4 4	3 5	2 8	2 4	4 0	3 2	2 7	2 2	1 9	
			0 . 6	0 . 8	6 1	4 9	4 1	3 5	5 8	4 7	4 0	3 4	5 3	4 4	3 7	3 2	4 8	4 0	3 5	3 0	2 6	
			0 . 5 6	1 . 0	6 7	5 6	4 8	4 2	6 4	5 4	4 7	4 1	5 8	5 0	4 3	3 9	5 3	4 6	4 1	3 6	3 2	
			1 . 2 5	7 3	6 3	5 5	4 9	7 0	6 0	5 3	4 8	6 3	5 6	5 0	4 5	5 7	5 1	4 6	4 2	3 7		
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	7 7	6 8	6 1	5 5	7 4	6 5	5 9	5 3	6 7	6 0	5 5	5 0	6 1	5 5	5 1	4 7	4 1		
			2 . 0	8 3	7 5	6 8	6 3	7 9	7 2	6 6	6 1	7 2	6 7	6 2	5 7	6 6	6 1	5 7	5 4	4 7		
取付 高さ	器具間隔最大限		2 . 5	8 6	8 0	7 4	6 9	8 3	7 7	7 1	6 7	7 6	7 1	6 6	6 3	6 9	6 5	6 2	5 9	5 2		
	横方向 (A) 縦方向 (B)		3 . 0	8 9	8 3	7 8	7 3	8 5	8 0	7 5	7 1	7 8	7 4	7 0	6 6	7 2	6 8	6 5	6 2	5 5		
H m	1 . 3 1 H m	1 . 3 1 H m	4 . 0	9 2	8 7	8 3	7 9	8 9	8 4	8 0	7 7	8 1	7 8	7 5	7 2	7 5	7 2	6 9	6 7	5 9		
			5 . 0	9 4	9 0	8 7	8 3	9 1	8 7	8 4	8 1	8 3	8 1	7 8	7 5	7 7	7 4	7 2	7 0	6 2		
			7 . 0	9 7	9 4	9 1	8 8	9 3	9 0	8 8	8 5	8 6	8 4	8 2	8 0	7 9	7 7	7 6	7 4	6 6		
			1 0 . 0	9 9	9 6	9 4	9 2	9 5	9 3	9 1	8 9	8 8	8 6	8 5	8 3	8 1	8 0	7 8	7 7	6 9		

