

屋内照明器具特性	
品番 (品名)	HH-CD0893AS
光源	LED6200_70_3800 ×1 3800.0lm
管理番号	K0163083(0)D 1
BZ分類	BZ6

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %					10 %					10 %					10 %					0 %	
上方光束		29 %	室指数	照明率 (X0.01)																				Z	C	M
下方光束		71 %																								
保守率		良 中 否	0.63	0.6	50	37	29	24	47	35	28	23	41	32	26	21	37	29	23	19	16					
			0.6	0.8	59	47	38	32	55	44	37	31	49	40	34	29	44	36	31	27	22					
			0.56	1.0	65	54	45	39	61	51	43	38	55	46	40	35	48	42	36	32	27					
				1.25	71	60	52	46	67	57	50	44	60	52	46	41	53	47	42	38	31					
下方投影面積		cm ²	1.5	75	65	58	52	71	62	55	50	63	56	50	46	56	51	46	42	35						
等価発光面積			cm ²	2.0	81	72	65	60	76	69	63	58	68	62	57	53	61	56	52	49	41					
取付 高さ	器具間隔最大限		2.5	84	77	71	66	80	73	68	63	72	67	62	58	64	60	57	53	45						
	横方向 (A)		縦方向 (B)		3.0	87	80	75	70	83	77	72	67	74	70	66	62	67	63	60	57	48				
H m	1.35 H m	1.35 H m	4.0	90	85	80	76	86	81	77	73	78	74	71	67	70	67	64	62	53						
			5.0	92	88	84	80	88	84	81	77	80	77	74	71	72	69	67	65	56						
			7.0	95	92	88	86	91	88	85	82	82	80	78	75	74	73	71	69	59						
			10.0	97	94	92	90	93	90	88	86	84	83	81	79	76	75	74	72	62						

