

屋内照明器具特性	
品番 (品名)	HH- CK0825CA
光源	LED6200_70_4299 ×1 4299.0 lm
管理番号	K0184947 (0) D 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		7 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		93 %																							
保守率		良 中 否	0.63	0.6	55	43	35	30	54	42	35	30	51	41	34	29	48	39	33	29	26				
			0.6	0.8	65	53	45	40	63	52	45	39	60	50	44	39	56	48	42	38	35				
			0.56	1.0	72	61	53	47	69	59	52	46	66	57	51	46	62	55	49	45	42				
			1.25	77	67	60	54	75	66	59	54	71	63	57	52	68	61	56	51	48					
下方投影面積		cm ²	1.5	81	72	65	60	79	71	64	59	75	68	62	58	71	65	60	56	53					
			2.0	87	79	73	68	85	78	72	67	81	75	70	65	77	72	67	64	60					
等価発光面積	cm ²	2.5	91	84	78	74	88	82	77	73	84	79	75	71	80	76	72	69	65						
		3.0	93	87	82	78	91	85	81	77	87	82	78	75	83	79	76	73	69						
H	m	1.26 H	m	1.26 H	m	4.0	96	92	87	84	94	90	86	82	90	86	83	80	78	74					
						5.0	98	94	91	87	96	92	89	86	92	89	86	84	88	84					
						7.0	100	97	95	92	98	96	93	91	94	92	90	88	91	87					
						10.0	102	100	98	96	100	98	96	94	96	95	93	91	92	88					

