

屋内照明器具特性	
品番 (品名)	HH- CK1010RDS
光源	LED6200_70_4899 ×1 4899.0 lm
管理番号	K0184692 (0) D 1
BZ分類	BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	5 5	4 3	3 5	2 9	5 3	4 2	3 4	2 9	5 0	4 0	3 3	2 9	4 7	3 8	3 2	2 8	2 6
			0 . 6	0 . 8	6 5	5 3	4 5	3 9	6 3	5 2	4 4	3 9	5 9	5 0	4 3	3 8	5 6	4 8	4 2	3 7	3 4
			0 . 5 6	1 . 0	7 1	6 0	5 2	4 6	6 9	5 9	5 1	4 6	6 5	5 6	5 0	4 5	6 1	5 4	4 8	4 4	4 1
				1 . 2 5	7 7	6 7	5 9	5 4	7 5	6 5	5 8	5 3	7 0	6 3	5 7	5 2	6 7	6 0	5 5	5 0	4 7
下方投影面積 等価発光面積		c m ²	1 . 5	8 1	7 2	6 5	5 9	7 9	7 0	6 4	5 8	7 4	6 7	6 2	5 7	7 0	6 4	5 9	5 5	5 2	
			2 . 0	8 7	7 9	7 2	6 7	8 4	7 7	7 1	6 6	8 0	7 4	6 9	6 4	7 6	7 1	6 6	6 3	5 9	
			2 . 5	9 0	8 3	7 8	7 3	8 8	8 2	7 6	7 2	8 3	7 8	7 4	7 0	7 9	7 5	7 1	6 8	6 4	
取付 高さ	器具間隔最大限		3 . 0	9 3	8 7	8 2	7 7	9 0	8 5	8 0	7 6	8 6	8 1	7 7	7 4	8 2	7 8	7 4	7 1	6 7	
	横方向 (A)	縦方向 (B)	4 . 0	9 6	9 1	8 7	8 3	9 3	8 9	8 5	8 2	8 9	8 5	8 2	7 9	8 5	8 2	7 9	7 7	7 2	
H m	1 . 2 5 H m	1 . 2 5 H m	5 . 0	9 8	9 4	9 0	8 7	9 5	9 2	8 8	8 5	9 1	8 8	8 5	8 3	8 7	8 4	8 2	8 0	7 5	
			7 . 0	1 0 0	9 7	9 4	9 2	9 8	9 5	9 2	9 0	9 3	9 1	8 9	8 7	8 9	8 7	8 6	8 4	7 9	
			1 0 . 0	1 0 2	1 0 0	9 7	9 5	1 0 0	9 8	9 6	9 4	9 5	9 4	9 2	9 0	9 1	9 0	8 9	8 7	8 2	

