

屋内照明器具特性	
品番 (品名)	HH- CM1 2 4 2 AS
光源	LED6200_70_5200 ×1 5200.0 lm
管理番号	K0193331 (0) D 1
BZ分類	BZ5

器具効率		100 % 上方光束 14 % 下方光束 86 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.63	0.6	54	42	35	29	52	41	34	29	49	39	33	28	45	37	31	27	24	
			0.6	0.8	64	53	45	39	62	51	44	38	57	48	42	37	53	46	40	36	33	
			0.56	1.0	70	60	52	46	68	58	51	45	63	55	49	44	59	52	47	42	39	
				1.25	76	67	59	53	74	65	58	53	69	61	55	51	64	58	53	49	45	
下方投影面積		cm ²	1.5	80	71	64	59	78	69	63	58	72	66	60	56	68	62	57	54	49		
			2.0	86	78	72	67	83	76	71	66	78	72	67	63	73	68	64	61	56		
等価発光面積		cm ²	2.5	89	83	77	73	87	81	76	71	81	76	72	68	76	72	69	65	60		
			3.0	92	86	81	77	89	84	79	75	84	79	76	72	78	75	72	69	64		
H m		1.26 H m	1.26 H m	4.0	95	90	86	83	92	88	84	81	87	83	80	77	82	79	76	74		
				5.0	97	93	90	86	94	91	87	85	89	86	83	81	84	81	79	77		
				7.0	99	96	94	91	96	94	91	89	91	89	87	85	86	84	83	81		
				10.0	101	99	97	95	98	96	94	93	93	91	90	88	88	86	85	84		

