

屋内照明器具特性	
品番 (品名)	HH- CM1 2 4 5 AS
光源	LED6200_70_5499 ×1 5499.0 lm
管理番号	K0193333 (0) D 1
B Z 分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		5 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		95 %																								
保守率		良 中 否	0.63	0.6	55	43	35	29	53	42	34	29	50	40	33	28	48	39	33	28	26					
			0.6	0.8	65	53	45	39	63	52	44	39	60	50	43	38	57	48	42	38	35					
			0.56	1.0	71	60	52	46	69	59	52	46	66	57	50	45	62	55	49	44	42					
				1.25	77	67	60	54	75	66	59	53	71	63	57	52	68	61	56	51	48					
下方投影面積		cm ²	1.5	81	72	65	59	79	71	64	59	75	68	62	57	72	66	61	56	53						
			2.0	87	79	73	67	85	78	72	67	81	75	70	65	77	72	68	64	60						
取付高さ	器具間隔最大限		2.5	91	84	78	73	88	82	77	72	84	79	75	71	81	76	72	69	65						
	横方向 (A) 縦方向 (B)		3.0	93	87	82	77	91	85	81	77	87	82	78	75	83	79	76	73	69						
H m	1.29 H m 1.29 H m		4.0	96	91	87	83	94	90	86	82	90	87	83	80	87	84	81	78	74						
			5.0	98	94	91	87	96	93	89	86	92	89	86	84	89	86	84	82	78						
			7.0	101	98	95	92	99	96	93	91	95	93	90	88	91	89	88	86	82						
			10.0	102	100	98	96	101	98	96	95	97	95	93	92	93	92	91	89	85						

