

屋内照明器具特性	
品番 (品名)	HH- J C C 1 2 4 2 A S
光源	LED6200_70_5499 ×1 5499.0 l m
管理番号	K0153257 (0) D 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		1 7 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		8 3 %																							
保守率		良	0 . 6 3	0 . 6	5 4	4 2	3 4	2 9	5 2	4 1	3 4	2 8	4 8	3 8	3 2	2 7	4 4	3 6	3 0	2 6	2 3				
		中	0 . 6	0 . 8	6 4	5 2	4 4	3 9	6 1	5 1	4 3	3 8	5 6	4 8	4 1	3 7	5 2	4 5	3 9	3 5	3 2				
		否	0 . 5 6	1 . 0	7 0	5 9	5 2	4 6	6 7	5 8	5 1	4 5	6 2	5 4	4 8	4 3	5 8	5 1	4 6	4 1	3 7				
		1 . 2 5	7 6	6 6	5 9	5 3	7 3	6 4	5 7	5 2	6 8	6 0	5 5	5 0	6 3	5 7	5 2	4 8	4 3						
下方投影面積		c m ²		1 . 5	8 0	7 1	6 4	5 9	7 7	6 9	6 3	5 7	7 1	6 5	5 9	5 5	6 6	6 1	5 6	5 2	4 8				
等価発光面積		c m ²		2 . 0	8 5	7 8	7 2	6 7	8 2	7 6	7 0	6 5	7 7	7 1	6 6	6 2	7 1	6 7	6 3	5 9	5 4				
取付高さ	器具間隔最大限			2 . 5	8 9	8 3	7 7	7 3	8 6	8 0	7 5	7 1	8 0	7 5	7 1	6 7	7 4	7 1	6 7	6 4	5 8				
	横方向 (A)		縦方向 (B)	3 . 0	9 1	8 6	8 1	7 7	8 8	8 3	7 9	7 5	8 2	7 8	7 4	7 1	7 7	7 3	7 0	6 8	6 2				
H m	1 . 2 7 H m	1 . 2 7 H m	4 . 0	9 4	9 0	8 6	8 2	9 1	8 7	8 4	8 0	8 5	8 2	7 9	7 6	8 0	7 7	7 5	7 2	6 6					
			5 . 0	9 6	9 3	8 9	8 6	9 3	9 0	8 7	8 4	8 7	8 5	8 2	8 0	8 2	7 9	7 7	7 5	6 9					
			7 . 0	9 9	9 6	9 3	9 1	9 5	9 3	9 1	8 8	9 0	8 7	8 5	8 4	8 4	8 2	8 1	7 9	7 2					
			1 0 . 0	1 0 0	9 8	9 6	9 4	9 7	9 5	9 4	9 2	9 1	9 0	8 8	8 7	8 6	8 4	8 3	8 2	7 5					

