

屋内照明器具特性	
品番 (品名)	HH- P A0831D
光源	LED6200_70_3700 ×1 3700.0 lm
管理番号	K0142077 (0) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
						室指数	照明率 (X0.01)																			
保守率		良 中 否	0.67	0.6	55	43	35	30	54	42	35	29	50	40	34	29	48	39	33	28	26					
			0.63	0.8	65	53	46	40	63	52	45	39	59	50	44	39	56	48	42	38	35					
			0.56	1.0	72	61	53	47	70	60	52	47	66	57	51	46	62	55	49	45	42					
			下方投影面積 等価発光面積	cm ² cm ²	1.25	78	68	60	55	75	66	59	54	71	64	58	53	67	61	56	52	48				
1.5	82	73			66	60	79	71	65	60	75	68	63	58	71	66	61	57	53							
2.0	87	80			74	69	85	78	73	68	81	75	70	66	77	72	68	64	61							
2.5	91	85			79	75	89	83	78	74	84	80	75	72	80	76	73	70	66							
取付 高さ	器具間隔最大限		2.5	91	85	79	75	89	83	78	74	84	80	75	72	80	76	73	70	66						
	横方向 (A)	縦方向 (B)	3.0	93	88	83	79	91	86	82	78	87	83	79	76	83	79	76	73	69						
H m	1.26 H m	1.26 H m	4.0	97	92	88	85	94	90	87	83	90	87	84	81	86	83	81	79	74						
			5.0	99	95	92	89	96	93	90	87	92	89	87	84	88	86	84	82	77						
			7.0	101	98	96	93	99	96	94	92	95	93	91	89	91	89	87	86	81						
			10.0	103	101	99	97	100	99	97	95	96	95	93	92	93	91	90	89	84						

