

屋内照明器具特性	
品番 (品名)	HH- SB0096N
光源	LED5000_70_415 ×1 415.0 lm
管理番号	K0172990 (0) DR 1
B Z 分類	BZ5

器具効率	100 % 上方光束 1 % 下方光束 99 %	天井	80 %				70 %				50 %				30 %				0 %
		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		壁	10 %				10 %				10 %				10 %				0 %
		床	照明率 (X0.01)				Z CM												
保守率	良 0.67 中 0.63 否 0.56	室指数	5.7	4.5	3.8	3.2	5.6	4.5	3.7	3.2	5.4	4.4	3.7	3.2	5.1	4.2	3.6	3.2	3.0
		0.6	5.7	4.5	3.8	3.2	5.6	4.5	3.7	3.2	5.4	4.4	3.7	3.2	5.1	4.2	3.6	3.2	3.0
		0.8	6.7	5.6	4.8	4.3	6.6	5.5	4.8	4.2	6.3	5.4	4.7	4.2	6.0	5.2	4.6	4.2	4.0
		1.0	7.4	6.3	5.6	5.0	7.2	6.2	5.5	5.0	6.9	6.1	5.4	4.9	6.6	5.9	5.3	4.9	4.7
下方投影面積 等価発光面積	c m ² c m ²	1.25	8.0	7.0	6.3	5.7	7.8	6.9	6.2	5.7	7.5	6.7	6.1	5.6	7.2	6.5	6.0	5.6	5.3
		1.5	8.4	7.5	6.8	6.3	8.2	7.4	6.8	6.2	7.9	7.2	6.6	6.2	7.6	7.0	6.5	6.1	5.9
		2.0	8.9	8.2	7.6	7.1	8.8	8.1	7.5	7.1	8.4	7.9	7.4	7.0	8.1	7.6	7.2	6.9	6.6
		2.5	9.3	8.6	8.1	7.7	9.1	8.5	8.0	7.6	8.8	8.3	7.9	7.5	8.5	8.1	7.7	7.4	7.1
取付高さ H m	器具間隔最大限		3.0	9.5	9.0	8.5	8.1	9.3	8.8	8.4	8.0	9.0	8.6	8.2	7.9	8.7	8.4	8.0	7.8
	横方向 (A)	縦方向 (B)	4.0	9.8	9.4	9.0	8.6	9.7	9.2	8.9	8.6	9.3	9.0	8.7	8.4	9.1	8.8	8.5	8.3
	1.22 H m	1.22 H m	5.0	10.0	9.6	9.3	9.0	9.8	9.5	9.2	8.9	9.5	9.3	9.0	8.8	9.3	9.0	8.8	8.6
			7.0	10.2	9.9	9.7	9.4	10.1	9.8	9.6	9.4	9.8	9.6	9.4	9.2	9.5	9.3	9.1	9.0
			10.0	10.4	10.2	10.0	9.8	10.2	10.1	9.9	9.7	10.0	9.8	9.6	9.5	9.7	9.6	9.4	9.3

