

屋内照明器具特性	
品番 (品名)	HH- SB0097L
光源	LED2700_70_726 ×1 726.0 lm
管理番号	K0172983 (0) DR 1
BZ分類	BZ5

器具効率		100 % 上方光束 1 % 下方光束 99 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	57	45	38	32	56	45	37	32	54	44	37	32	51	42	36	32	30	
			0.63	0.8	67	56	48	43	66	55	48	42	63	54	47	42	60	52	46	42	40	
			0.56	1.0	74	63	56	50	72	62	55	50	69	61	54	49	66	59	53	49	46	
				1.25	80	70	63	57	78	69	62	57	75	67	61	56	72	65	60	56	53	
下方投影面積 等価発光面積		cm ² cm ²		1.5	84	75	68	63	82	74	67	62	79	72	66	62	76	70	65	61	58	
				2.0	89	82	76	71	87	81	75	70	84	78	74	69	81	76	72	68	66	
取付 高さ	器具間隔最大限				2.5	93	86	81	76	91	85	80	76	88	83	78	75	85	80	77	74	71
	横方向 (A)		縦方向 (B)		3.0	95	89	85	81	93	88	84	80	90	86	82	79	87	83	80	77	75
H m	1.22 H m		1.22 H m		4.0	98	94	90	86	96	92	89	85	93	90	87	84	90	88	85	82	79
					5.0	100	96	93	90	98	95	92	89	95	92	90	87	92	90	88	86	83
					7.0	102	99	97	94	101	98	96	93	98	95	93	92	95	93	91	90	87
					10.0	104	102	100	98	102	100	99	97	99	98	96	95	97	95	94	93	90

