

屋内照明器具特性	
品番 (品名)	HH-SD0024N
光源	LED5000_70_953 ×1 953.0 lm
管理番号	K0161584 (0) DB1
BZ分類	BZ5

器具効率		1 0 0 % 上方光束 6 % 下方光束 9 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6	5 5	4 2	3 4	2 9	5 3	4 1	3 4	2 8	5 0	4 0	3 3	2 8	4 7	3 8	3 2	2 7	2 5	
			0 . 6	6 4	5 2	4 4	3 8	6 2	5 1	4 4	3 8	5 9	4 9	4 2	3 7	5 6	4 7	4 1	3 7	3 4	
			1 . 0	7 1	5 9	5 1	4 5	6 9	5 8	5 1	4 5	6 5	5 6	4 9	4 4	6 1	5 4	4 8	4 3	4 0	
			0 . 5 6	1 . 2 5	7 6	6 6	5 8	5 2	7 4	6 5	5 8	5 2	7 0	6 2	5 6	5 1	6 7	6 0	5 4	5 0	4 6
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 0	7 1	6 4	5 8	7 8	7 0	6 3	5 7	7 4	6 7	6 1	5 6	7 0	6 4	5 9	5 5	5 1	
			2 . 0	8 6	7 8	7 1	6 6	8 4	7 6	7 0	6 5	8 0	7 3	6 8	6 4	7 6	7 0	6 6	6 2	5 8	
			2 . 5	9 0	8 3	7 7	7 2	8 7	8 1	7 5	7 1	8 3	7 8	7 3	6 9	7 9	7 5	7 1	6 7	6 3	
取付 高さ	器具間隔最大限		3 . 0	9 2	8 6	8 1	7 6	9 0	8 4	7 9	7 5	8 6	8 1	7 7	7 3	8 2	7 8	7 4	7 1	6 7	
	横方向 (A)	縦方向 (B)	4 . 0	9 5	9 0	8 6	8 2	9 3	8 9	8 4	8 1	8 9	8 5	8 2	7 8	8 5	8 2	7 9	7 6	7 2	
H m	1 . 2 5 H m	1 . 2 5 H m	5 . 0	9 7	9 3	8 9	8 6	9 5	9 1	8 8	8 5	9 1	8 8	8 5	8 2	8 7	8 5	8 2	8 0	7 6	
			7 . 0	1 0 0	9 7	9 4	9 1	9 8	9 5	9 2	8 9	9 4	9 1	8 9	8 7	9 0	8 8	8 6	8 4	8 0	
			1 0 . 0	1 0 2	9 9	9 7	9 5	1 0 0	9 8	9 5	9 3	9 6	9 4	9 2	9 0	9 2	9 1	8 9	8 8	8 3	

