

屋内照明器具特性	
品番 (品名)	HH-SF0013L
光源	LDA4L-H-E17/E/S/W/2×1 440.0lm
管理番号	K0125729(1)DB1
BZ分類	BZ10

器具効率		57 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		27 %	室指数	照明率 (X0.01)																			Z C M	
下方光束		30 %																						
保守率		良 中 否	0.63	0.6	2.4	1.7	1.2	9	2.2	1.5	1.1	8	1.8	1.3	9	6	1.4	1.0	7	5	2			
			0.6	0.8	2.9	2.1	1.6	1.3	2.6	2.0	1.5	1.2	2.1	1.6	1.2	1.0	1.7	1.3	1.0	8	4			
			0.56	1.0	3.2	2.5	2.0	1.6	2.9	2.3	1.8	1.5	2.4	1.9	1.5	1.2	1.9	1.5	1.2	1.0	5			
				1.25	3.5	2.8	2.3	1.9	3.2	2.6	2.2	1.8	2.6	2.2	1.8	1.5	2.1	1.7	1.4	1.2	7			
下方投影面積		c m ²	1.5	3.8	3.1	2.6	2.2	3.4	2.9	2.4	2.1	2.8	2.4	2.0	1.7	2.3	1.9	1.6	1.4	9				
等価発光面積			c m ²	2.0	4.1	3.5	3.1	2.7	3.8	3.3	2.8	2.5	3.1	2.7	2.4	2.1	2.5	2.2	2.0	1.7	1.1			
取付高さ	器具間隔最大限			2.5	4.3	3.8	3.4	3.0	4.0	3.5	3.1	2.8	3.3	3.0	2.7	2.4	2.7	2.4	2.2	2.0	1.3			
横方向 (A)		縦方向 (B)		3.0	4.5	4.0	3.6	3.3	4.1	3.7	3.4	3.1	3.5	3.1	2.9	2.6	2.8	2.6	2.4	2.2	1.4			
H m	0.00 H m	0.00 H m	4.0	4.7	4.3	4.0	3.7	4.3	4.0	3.7	3.4	3.6	3.4	3.1	2.9	3.0	2.8	2.6	2.4	1.7				
			5.0	4.8	4.5	4.2	3.9	4.5	4.2	3.9	3.7	3.8	3.5	3.3	3.1	3.1	2.9	2.8	2.6	1.8				
			7.0	5.0	4.7	4.5	4.3	4.6	4.4	4.2	4.0	3.9	3.8	3.6	3.4	3.3	3.1	3.0	2.9	2.1				
			10.0	5.1	4.9	4.7	4.6	4.8	4.6	4.4	4.3	4.1	3.9	3.8	3.7	3.4	3.3	3.2	3.1	2.2				

