

屋内照明器具特性	
品番 (品名)	HH- S F 0 0 1 8 L
光源	LED2700_70_500 ×1 500.0 l m
管理番号	K0160458 (0) DB 1
B Z 分類	BZ5

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6	5 7	4 4	3 7	3 1	5 5	4 4	3 6	3 1	5 3	4 3	3 6	3 1	5 1	4 2	3 5	3 1	2 9	
			0 . 8	6 7	5 5	4 7	4 2	6 5	5 4	4 7	4 2	6 2	5 3	4 6	4 1	6 0	5 2	4 6	4 1	3 9	
			1 . 0	7 3	6 3	5 5	4 9	7 2	6 2	5 5	4 9	6 9	6 0	5 4	4 9	6 6	5 9	5 3	4 8	4 6	
			1 . 2 5	7 9	7 0	6 2	5 7	7 8	6 9	6 2	5 6	7 5	6 7	6 1	5 6	7 2	6 5	6 0	5 6	5 3	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 4	7 5	6 8	6 2	8 2	7 4	6 7	6 2	7 9	7 2	6 6	6 1	7 6	7 0	6 5	6 1	5 8	
			2 . 0	8 9	8 2	7 6	7 1	8 8	8 1	7 5	7 0	8 4	7 9	7 4	7 0	8 2	7 7	7 2	6 9	6 6	
			2 . 5	9 3	8 6	8 1	7 7	9 1	8 5	8 0	7 6	8 8	8 3	7 9	7 5	8 5	8 1	7 7	7 4	7 2	
取付 高さ	器具間隔最大限		3 . 0	9 5	9 0	8 5	8 1	9 4	8 9	8 4	8 0	9 1	8 6	8 3	7 9	8 8	8 4	8 1	7 8	7 5	
	横方向 (A)	縦方向 (B)	4 . 0	9 8	9 4	9 0	8 7	9 7	9 3	8 9	8 6	9 4	9 1	8 7	8 5	9 1	8 8	8 6	8 3	8 1	
H m	1 . 2 7 H m	1 . 2 7 H m	5 . 0	1 0 0	9 7	9 3	9 0	9 9	9 5	9 2	9 0	9 6	9 3	9 1	8 8	9 3	9 1	8 9	8 7	8 4	
			7 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 9	9 6	9 4	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 1	8 8	
			1 0 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 8	9 6	9 5	9 4	9 1	

