

屋内照明器具特性	
品番 (品名)	HH- S H0 0 2 1 L
光源	LDA7 L - G / S / K6 ×1 810.0 lm
管理番号	K0169054 (0) DB 1
B Z 分類	BZ7 / 0.7 / BZ6

器具効率		86 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		26 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		60 %		室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.69	0.6	42	31	24	19	39	29	23	18	34	26	21	17	30	23	19	15	12
			0.67	0.8	49	39	31	26	46	37	30	25	41	33	27	23	36	29	25	21	17
			0.63	1.0	54	44	37	32	51	42	35	30	45	38	32	28	40	34	29	25	20
			0.63	1.25	59	50	43	37	56	47	41	36	49	42	37	33	43	38	33	30	24
下方投影面積		cm ²	1.5	63	54	47	42	59	51	45	40	52	46	41	36	46	41	37	33	27	
等価発光面積		cm ²	2.0	68	60	54	48	64	57	51	46	57	51	46	42	50	46	42	39	32	
取付 高さ	器具間隔最大限		2.5	71	64	58	53	67	61	56	51	60	55	50	47	53	49	45	42	35	
	横方向 (A) 縦方向 (B)		3.0	73	67	62	57	69	64	59	55	62	57	53	50	55	51	48	45	38	
H m	1.39 H m	1.39 H m	4.0	76	71	67	63	72	68	63	60	65	61	58	55	58	55	52	50	41	
			5.0	78	74	70	66	74	70	67	63	66	63	60	58	59	57	55	52	44	
			7.0	80	77	74	71	76	73	70	68	69	66	64	62	62	60	58	56	47	
			10.0	82	79	77	75	78	76	74	72	71	69	67	65	64	62	61	59	50	

