

屋内照明器具特性	
品番 (品名)	LGB10883
光源	LED2700_70_341 x1 341.0 lm
管理番号	K0146454 (0) DB1
BZ分類	BZ5/2.8/BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		13 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		87 %																								
保守率		良 中 否	0.63	0.6	53	41	33	28	52	40	33	27	48	38	31	26	45	36	30	26	23					
			0.6	0.8	63	51	43	37	60	49	42	36	56	47	40	35	52	44	38	34	31					
			0.56	1.0	69	58	50	44	66	56	49	43	62	53	46	41	58	50	44	40	36					
				1.25	75	64	56	50	72	62	55	49	67	59	53	48	62	56	50	46	42					
下方投影面積		cm ²	1.5	79	69	61	55	76	67	60	54	71	63	57	52	66	60	55	50	46						
等価発光面積		cm ²	2.0	84	76	69	63	81	74	67	62	76	70	64	60	71	66	61	57	53						
取付 高さ	器具間隔最大限		2.5	88	80	74	69	85	78	72	68	79	74	69	65	74	70	66	62	57						
	横方向 (A)	縦方向 (B)	3.0	90	84	78	73	87	81	76	72	82	77	73	69	77	73	69	66	61						
H m	0.87 H m	0.92 H m	4.0	93	88	83	79	91	86	81	77	85	81	77	74	80	77	74	71	65						
			5.0	96	91	87	83	93	89	85	81	87	84	81	78	82	79	77	74	69						
			7.0	98	94	91	88	95	92	89	86	90	87	85	82	85	83	81	79	73						
			10.0	100	97	95	92	97	95	93	90	92	90	88	86	87	85	84	82	76						

