

屋内照明器具特性	
品番 (品名)	L G B 1 0 9 3 7
光源	LED2700_70_138 ×1 138.0 l m
管理番号	K0138378 (0) DB 1
B Z 分類	BZ4 / 1.8 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		1 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		9 0 %																				
保守率		良 中 否	0 . 6 7	0 . 6	6 0	4 9	4 1	3 7	5 8	4 8	4 1	3 6	5 5	4 6	4 0	3 6	5 2	4 4	3 9	3 5	3 3	
			0 . 6 3	0 . 8	6 8	5 8	5 0	4 5	6 6	5 6	5 0	4 5	6 3	5 4	4 8	4 4	5 9	5 2	4 7	4 3	4 0	
			0 . 5 6	1 . 0	7 4	6 4	5 7	5 1	7 2	6 2	5 6	5 1	6 8	6 0	5 4	5 0	6 4	5 7	5 2	4 8	4 5	
				1 . 2 5	7 9	7 0	6 3	5 8	7 7	6 8	6 2	5 7	7 2	6 5	6 0	5 5	6 9	6 3	5 8	5 4	5 1	
下方投影面積		cm ²	等価発光面積 cm ²	1 . 5	8 3	7 4	6 8	6 2	8 0	7 2	6 6	6 1	7 6	6 9	6 4	6 0	7 2	6 6	6 2	5 8	5 4	
等価発光面積		cm ²		2 . 0	8 8	8 0	7 4	7 0	8 5	7 8	7 3	6 8	8 1	7 5	7 0	6 6	7 6	7 2	6 8	6 5	6 0	
取付高さ	器具間隔最大限			2 . 5	9 1	8 4	7 9	7 5	8 8	8 2	7 8	7 3	8 4	7 9	7 5	7 1	7 9	7 5	7 2	6 9	6 5	
	横方向 (A) 縦方向 (B)			3 . 0	9 3	8 7	8 3	7 8	9 0	8 5	8 1	7 7	8 6	8 2	7 8	7 5	8 2	7 8	7 5	7 2	6 8	
H m	0 . 8 9 H m	0 . 8 9 H m	4 . 0	9 6	9 1	8 7	8 4	9 3	8 9	8 6	8 2	8 9	8 5	8 2	7 9	8 4	8 2	7 9	7 7	7 2		
			5 . 0	9 8	9 4	9 0	8 7	9 5	9 2	8 9	8 6	9 1	8 8	8 5	8 3	8 6	8 4	8 2	8 0	7 5		
			7 . 0	1 0 0	9 7	9 4	9 2	9 7	9 5	9 2	9 0	9 3	9 1	8 9	8 7	8 9	8 7	8 5	8 3	7 8		
			1 0 . 0	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 5	9 3	9 1	9 0	9 0	8 9	8 8	8 6	8 1		

