

屋内照明器具特性	
品番 (品名)	L G B 1 0 9 7 8
光源	LED2700_70_313 ×1 313.0 lm
管理番号	K0138375 (0) DB 1
BZ分類	BZ7/0.7/BZ6

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		1 8 %	室指数	照明率 (X 0 . 0 1) Z C M																					
下方光束		8 2 %																							
保守率		良 中 否	0 . 6 7	0 . 6	5 0	3 7	2 9	2 3	4 7	3 5	2 8	2 2	4 3	3 3	2 6	2 1	3 9	3 1	2 4	2 0	1 7				
			0 . 6 3	0 . 8	5 9	4 7	3 8	3 2	5 7	4 5	3 7	3 1	5 2	4 2	3 5	3 0	4 7	3 9	3 3	2 8	2 4				
			0 . 5 6	1 . 0	6 6	5 4	4 5	3 9	6 3	5 2	4 4	3 8	5 7	4 8	4 1	3 6	5 2	4 5	3 9	3 4	3 0				
				1 . 2 5	7 2	6 1	5 3	4 6	6 9	5 9	5 1	4 5	6 3	5 4	4 8	4 3	5 7	5 0	4 5	4 0	3 6				
下方投影面積		cm ²	等価発光面積 cm ²	1 . 5	7 6	6 6	5 8	5 2	7 3	6 4	5 6	5 0	6 7	5 9	5 3	4 8	6 1	5 5	5 0	4 5	4 0				
等価発光面積		cm ²		2 . 0	8 2	7 3	6 6	6 0	7 9	7 1	6 4	5 9	7 2	6 6	6 0	5 5	6 6	6 1	5 6	5 2	4 7				
取付高さ	器具間隔最大限			2 . 5	8 6	7 8	7 2	6 6	8 2	7 5	6 9	6 4	7 6	7 0	6 5	6 1	7 0	6 5	6 1	5 7	5 1				
	横方向 (A) 縦方向 (B)			3 . 0	8 8	8 2	7 6	7 1	8 5	7 9	7 3	6 9	7 8	7 3	6 9	6 5	7 2	6 8	6 5	6 1	5 5				
H m	1 . 0 4 H m	1 . 0 4 H m	4 . 0	9 2	8 6	8 1	7 7	8 8	8 3	7 9	7 5	8 2	7 8	7 4	7 1	7 6	7 3	6 9	6 7	6 0					
			5 . 0	9 4	8 9	8 5	8 1	9 1	8 6	8 2	7 9	8 4	8 1	7 7	7 4	7 8	7 5	7 3	7 0	6 3					
			7 . 0	9 7	9 3	9 0	8 6	9 3	9 0	8 7	8 4	8 7	8 4	8 2	7 9	8 1	7 9	7 7	7 5	6 7					
			1 0 . 0	9 9	9 6	9 3	9 1	9 5	9 3	9 1	8 8	8 9	8 7	8 5	8 3	8 3	8 1	8 0	7 8	7 1					

