

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | L G B 1 6 2 4 2             |
| 光源       | LED2700_70_415 ×1 415.0 l m |
| 管理番号     | K0151381 ( 0 ) DB 1         |
| B Z 分類   | B Z 5                       |

| 器具効率   |           | 100 %           | 反射率             | 天井            | 80 % |    |    |     | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |    |   |   |   |
|--------|-----------|-----------------|-----------------|---------------|------|----|----|-----|------|----|----|----|------|----|----|----|------|----|----|----|-----|----|---|---|---|
|        |           |                 |                 | 壁             | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |    |   |   |   |
|        |           |                 |                 | 床             | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |    |   |   |   |
| 上方光束   |           | 4 %             | 室指数             | 照明率 ( X0.01 ) |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |    | Z | C | M |
| 下方光束   |           | 96 %            |                 |               |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |    |   |   |   |
| 保守率    |           | 良<br>中<br>否     | 0.63            | 0.6           | 56   | 43 | 35 | 30  | 54   | 42 | 35 | 30 | 51   | 41 | 34 | 29 | 49   | 40 | 34 | 29 | 27  |    |   |   |   |
|        |           |                 | 0.6             | 0.8           | 65   | 54 | 46 | 40  | 64   | 53 | 45 | 40 | 61   | 51 | 44 | 39 | 58   | 50 | 43 | 39 | 36  |    |   |   |   |
|        |           |                 |                 | 1.0           | 72   | 61 | 53 | 47  | 70   | 60 | 53 | 47 | 67   | 58 | 52 | 46 | 64   | 56 | 50 | 46 | 43  |    |   |   |   |
|        |           |                 | 0.56            | 1.25          | 78   | 68 | 61 | 55  | 76   | 67 | 60 | 55 | 73   | 65 | 59 | 54 | 69   | 63 | 57 | 53 | 50  |    |   |   |   |
| 下方投影面積 |           | cm <sup>2</sup> |                 | 1.5           | 82   | 73 | 66 | 61  | 80   | 72 | 65 | 60 | 77   | 70 | 64 | 59 | 73   | 67 | 62 | 58 | 55  |    |   |   |   |
| 等価発光面積 |           |                 | cm <sup>2</sup> | 2.0           | 88   | 80 | 74 | 69  | 86   | 79 | 73 | 68 | 82   | 76 | 71 | 67 | 79   | 74 | 70 | 66 | 63  |    |   |   |   |
| 取付高さ   | 器具間隔最大限   |                 | 2.5             | 92            | 85   | 79 | 75 | 90  | 84   | 78 | 74 | 86 | 81   | 76 | 73 | 82 | 78   | 74 | 71 | 68 |     |    |   |   |   |
|        | 横方向 ( A ) |                 | 縦方向 ( B )       |               | 3.0  | 94 | 88 | 83  | 79   | 92 | 87 | 82 | 78   | 88 | 84 | 80 | 77   | 85 | 81 | 78 | 75  | 72 |   |   |   |
| H m    | 1.30 H m  | 1.30 H m        | 4.0             | 97            | 93   | 89 | 85 | 95  | 91   | 87 | 84 | 92 | 88   | 85 | 82 | 88 | 86   | 83 | 80 | 77 |     |    |   |   |   |
|        |           |                 | 5.0             | 99            | 95   | 92 | 89 | 97  | 94   | 91 | 88 | 94 | 91   | 88 | 86 | 91 | 88   | 86 | 84 | 80 |     |    |   |   |   |
|        |           |                 | 7.0             | 101           | 99   | 96 | 93 | 100 | 97   | 95 | 92 | 96 | 94   | 92 | 90 | 93 | 91   | 90 | 88 | 84 |     |    |   |   |   |
|        |           |                 | 10.0            | 103           | 101  | 99 | 97 | 101 | 100  | 98 | 96 | 98 | 97   | 95 | 94 | 95 | 94   | 92 | 91 | 87 |     |    |   |   |   |

