

屋内照明器具特性	
品番 (品名)	LGB16452
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 l m
管理番号	K0170957 (0) DR 1
BZ分類	BZ6/0.7/BZ5/1.1/BZ6

器具効率		98 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	50	39	31	26	48	37	30	25	43	34	28	23	39	31	26	22	18
			0.63	0.8	59	48	40	34	56	46	39	33	50	42	36	31	45	38	33	29	25
			0.56	1.0	65	54	46	41	62	52	45	39	55	47	41	37	50	43	38	34	29
				1.25	71	60	53	47	67	58	51	45	60	53	47	42	54	48	43	39	33
下方投影面積		cm ²	1.5	74	65	58	52	71	62	55	50	63	57	51	47	57	51	47	43	37	
			2.0	80	71	65	59	76	68	62	57	68	62	57	53	61	57	53	49	42	
等価発光面積		cm ²	2.5	83	76	70	65	79	72	67	62	71	66	62	58	64	60	56	53	46	
			3.0	85	79	73	69	81	76	71	66	74	69	65	61	66	63	59	56	48	
H m	1.34 H m	1.34 H m	4.0	88	83	79	74	84	80	75	72	77	73	69	66	69	66	63	61	52	
			5.0	90	86	82	78	86	82	79	75	79	75	72	69	71	69	66	64	55	
			7.0	93	89	86	83	89	86	83	80	81	78	76	74	74	72	70	68	59	
			10.0	95	92	90	87	91	88	86	84	83	81	79	77	76	74	73	71	62	

