

屋内照明器具特性		440.0lm
品番（品名）	LGB16454	
光源	LDA6-G-E17/KU/DN/S/W(N) x1	
管理番号	K0170956(0)DR1	
BZ分類	BZ6	

器具効率		96 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		29 % 67 %	室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.67	0.6	47	35	27	22	44	33	26	21	39	30	24	20	34	27	22	18	14
			0.63	0.8	56	44	36	31	53	42	35	29	46	38	32	27	41	34	29	25	20
			1.0	62	51	43	37	58	48	41	35	51	43	37	33	45	39	34	30	24	
			0.56	1.25	67	57	49	43	63	54	47	42	56	49	43	38	50	44	39	35	29
下方投影面積		cm ²	1.5	71	62	54	48	67	59	52	46	60	53	47	43	53	47	43	39	32	
等価発光面積		cm ²	2.0	76	68	62	56	72	65	59	54	64	58	53	49	57	52	48	45	37	
取付 高さ	器具間隔最大限		2.5	80	73	67	61	76	69	64	59	67	62	58	54	60	56	52	49	41	
	横方向 (A) 縦方向 (B)		3.0	82	76	70	66	78	72	67	63	70	65	61	57	62	58	55	52	43	
H m	1.50 H m	1.50 H m	4.0	86	80	76	71	81	76	72	68	73	69	66	62	65	62	59	57	47	
			5.0	88	83	79	75	83	79	75	72	75	72	69	66	67	64	62	60	50	
			7.0	90	87	83	80	86	82	79	77	77	75	72	70	69	67	65	63	53	
			10.0	92	89	87	84	88	85	83	81	79	77	75	74	71	70	68	67	56	

