

屋内照明器具特性	
品番 (品名)	L G B 1 9 2 3 5 B Z
光源	L D A 7 L - D - G / S / Z 6 × 2 8 1 0 . 0 l m
管理番号	K 0 1 5 5 0 5 9 (0) D B 1
B Z 分類	B Z 9

器具効率		7 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		3 6 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		4 3 %																				
保守率		良	0 . 6 3	0 . 6	3 4	2 4	1 8	1 3	3 1	2 2	1 6	1 2	2 6	1 9	1 4	1 0	2 1	1 5	1 1	8	4	
		中	0 . 6	0 . 8	4 1	3 1	2 4	1 9	3 7	2 9	2 2	1 8	3 1	2 4	1 9	1 5	2 5	1 9	1 5	1 2	7	
		否	0 . 5 6	1 . 0	4 6	3 6	2 9	2 4	4 2	3 3	2 7	2 2	3 5	2 8	2 3	1 9	2 8	2 3	1 9	1 5	9	
				1 . 2 5	5 0	4 1	3 4	2 9	4 6	3 8	3 2	2 7	3 8	3 2	2 7	2 3	3 1	2 6	2 2	1 9	1 2	
下方投影面積		c m ²		1 . 5	5 3	4 5	3 8	3 3	4 9	4 1	3 5	3 0	4 1	3 5	3 0	2 6	3 3	2 9	2 5	2 1	1 4	
等価発光面積		c m ²		2 . 0	5 8	5 0	4 4	3 9	5 3	4 6	4 1	3 6	4 5	3 9	3 5	3 1	3 7	3 2	2 9	2 6	1 7	
取付高さ	器具間隔最大限			2 . 5	6 1	5 4	4 8	4 4	5 6	5 0	4 5	4 1	4 7	4 2	3 8	3 5	3 9	3 5	3 2	2 9	2 0	
	横方向 (A)		縦方向 (B)	3 . 0	6 3	5 7	5 2	4 7	5 8	5 3	4 8	4 4	4 9	4 5	4 1	3 8	4 1	3 7	3 4	3 2	2 2	
H m	2 . 3 1 H m	2 . 3 2 H m	4 . 0	6 6	6 1	5 6	5 2	6 1	5 6	5 2	4 9	5 2	4 8	4 5	4 2	4 3	4 0	3 8	3 5	2 5		
			5 . 0	6 8	6 3	5 9	5 6	6 3	5 9	5 5	5 2	5 3	5 0	4 8	4 5	4 5	4 2	4 0	3 8	2 7		
			7 . 0	7 0	6 6	6 3	6 0	6 5	6 2	5 9	5 6	5 6	5 3	5 1	4 9	4 7	4 5	4 3	4 1	3 0		
			1 0 . 0	7 2	6 9	6 7	6 4	6 7	6 4	6 2	6 0	5 7	5 6	5 4	5 2	4 9	4 7	4 6	4 4	3 3		

