

屋内照明器具特性	
品番 (品名)	LGB19305Z
光源	LDA7L-G/S/K6 ×2 810.0 lm
管理番号	K0160392 (0) DR1
BZ分類	BZ5/1.4/BZ6

器具効率		56 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束 下方光束		19 % 37 %	室指数	照明率 (X0.01)																Z CM			
保守率		良 中 否	0.67	0.6	28	22	17	14	27	21	17	14	23	18	15	13	20	16	14	12	9		
			0.63	0.8	33	27	22	19	31	25	21	18	27	23	19	17	24	20	18	15	13		
			1.0	36	30	26	23	34	29	25	22	30	26	23	20	26	23	20	18	15			
			0.56	1.25	39	34	30	26	37	32	28	25	33	29	25	23	29	25	23	21	17		
下方投影面積 等価発光面積		cm ² cm ²	1.5	42	36	32	29	39	34	31	28	34	31	28	25	30	27	25	23	19			
			2.0	44	40	36	33	42	38	34	32	37	34	31	29	32	30	28	26	21			
取付 高さ	器具間隔最大限		2.5	46	42	39	36	44	40	37	34	39	36	33	31	34	32	30	28	23			
	横方向 (A) 縦方向 (B)		3.0	48	44	41	38	45	42	39	37	40	37	35	33	35	33	31	30	24			
H m	1.33 H m	1.33 H m	4.0	49	46	44	41	47	44	42	40	41	39	37	36	37	35	33	32	26			
			5.0	50	48	46	44	48	45	43	42	43	41	39	38	38	36	35	34	28			
			7.0	52	50	48	46	49	47	46	44	44	42	41	40	39	38	37	36	29			
			10.0	53	51	50	49	50	49	48	46	45	44	43	42	40	39	38	37	31			

