

屋内照明器具特性	
品番 (品名)	L G B 1 9 3 2 1 W U
光源	L D A (5 L D E 1 7 + 7 L D) S Z (2 8 7 0) × 1 2 8 7 0 . 0 1 m
管理番号	K 0 1 3 2 5 9 5 (0) D B 1
B Z 分類	B Z 8

器具効率		8 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		4 0 %	室指数	照明率 (X 0 . 0 1)																	Z C M	
下方光束		4 7 %																				
保守率		良 中 否	0 . 6 3	0 . 6	4 0	2 9	2 2	1 7	3 6	2 7	2 0	1 6	3 0	2 3	1 7	1 4	2 5	1 9	1 4	1 1	7	
			0 . 6	0 . 8	4 7	3 6	2 9	2 4	4 3	3 3	2 7	2 2	3 6	2 8	2 3	1 9	2 9	2 3	1 9	1 6	1 0	
			0 . 5 6	1 . 0	5 2	4 2	3 4	2 9	4 8	3 8	3 2	2 7	4 0	3 2	2 7	2 3	3 2	2 7	2 3	1 9	1 3	
				1 . 2 5	5 7	4 7	4 0	3 4	5 2	4 3	3 7	3 2	4 3	3 7	3 1	2 7	3 6	3 0	2 6	2 3	1 5	
下方投影面積		c m ²	1 . 5	6 0	5 1	4 4	3 8	5 5	4 7	4 1	3 6	4 6	4 0	3 5	3 1	3 8	3 3	2 9	2 6	1 7		
等価発光面積			c m ²	2 . 0	6 5	5 7	5 1	4 5	6 0	5 3	4 7	4 2	5 0	4 5	4 0	3 6	4 1	3 7	3 4	3 0	2 1	
取付高さ	器具間隔最大限		2 . 5	6 8	6 1	5 5	5 0	6 3	5 7	5 1	4 7	5 3	4 8	4 4	4 0	4 4	4 0	3 7	3 4	2 4		
	横方向 (A)		縦方向 (B)		3 . 0	7 0	6 4	5 9	5 4	6 5	5 9	5 5	5 0	5 5	5 1	4 7	4 3	4 6	4 2	3 9	3 7	2 6
H m	1 . 4 7 H m		1 . 4 4 H m		4 . 0	7 3	6 8	6 3	5 9	6 8	6 3	5 9	5 5	5 8	5 4	5 1	4 8	4 8	4 5	4 3	4 0	2 9
					5 . 0	7 5	7 1	6 7	6 3	7 0	6 6	6 2	5 9	6 0	5 6	5 4	5 1	5 0	4 7	4 5	4 3	3 1
					7 . 0	7 8	7 4	7 1	6 8	7 2	6 9	6 6	6 3	6 2	5 9	5 7	5 5	5 2	5 0	4 8	4 7	3 4
					1 0 . 0	8 0	7 7	7 4	7 2	7 4	7 2	6 9	6 7	6 4	6 2	6 0	5 8	5 4	5 2	5 1	5 0	3 7

