

屋内照明器具特性	
品番 (品名)	LGB50663
光源	LED3500_70_2420 ×1 2420.0 lm
管理番号	K0194360 (0) DR 1
BZ分類	BZ5

器具効率		100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	55	43	35	29	53	42	34	29	50	40	33	29	47	39	32	28	26	
			0.63	0.8	65	53	45	39	63	52	44	39	59	50	43	38	56	48	42	37	35	
			0.56	1.0	71	60	52	46	69	59	52	46	65	57	50	45	62	54	49	44	41	
				1.25	77	67	60	54	75	66	59	53	71	63	57	52	67	61	55	51	48	
下方投影面積		cm ²	1.5	81	72	65	59	79	71	64	59	75	68	62	57	71	65	60	56	52		
			等価発光面積	cm ²	2.0	87	79	73	67	84	77	71	67	80	74	69	65	76	71	67	63	59
取付 高さ	器具間隔最大限			2.5	90	84	78	73	88	82	77	72	84	79	74	70	80	75	72	68	64	
	横方向 (A)		縦方向 (B)	3.0	93	87	82	77	90	85	80	76	86	82	78	74	82	78	75	72	68	
1.5m	2.02 m	2.15 m	4.0	96	91	87	83	94	89	85	82	89	86	82	79	86	82	80	77	73		
2	2.67	2.72	5.0	98	94	90	87	96	92	89	86	92	88	86	83	88	85	83	80	76		
2.5	3.32	3.31	7.0	100	97	94	92	98	95	93	90	94	92	89	87	90	88	86	85	80		
3	3.96	3.91	10.0	102	100	98	95	100	98	96	94	96	94	92	91	92	91	89	88	83		

