

屋内照明器具特性

品番 (品名)	L G B 5 0 9 2 3									
光源	LED5000_70_835 x1 835.0 lm									
管理番号	K0154845 (0) DB 1									
B Z 分類	B Z 1 0									

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1)																				Z C M
保守率		良 中 否	0 . 6 9	0 . 6	4 3	2 9	2 1	1 5	3 9	2 7	1 9	1 4	3 1	2 2	1 6	1 1	2 5	1 7	1 2	8	3				
			0 . 6 7	0 . 8	5 1	3 7	2 8	2 2	4 6	3 4	2 6	2 0	3 7	2 8	2 1	1 6	3 0	2 2	1 7	1 3	6				
			0 . 6 3	1 . 0	5 6	4 4	3 5	2 8	5 1	4 0	3 2	2 5	4 2	3 3	2 6	2 1	3 3	2 6	2 1	1 6	9				
				1 . 2 5	6 2	5 0	4 1	3 4	5 6	4 6	3 7	3 1	4 6	3 8	3 1	2 6	3 7	3 0	2 5	2 1	1 1				
下方投影面積		c m ²		1 . 5	6 6	5 5	4 6	3 9	6 0	5 0	4 2	3 6	5 0	4 2	3 5	3 0	4 0	3 3	2 8	2 4	1 4				
			等価発光面積	c m ²	2 . 0	7 2	6 2	5 4	4 7	6 6	5 7	5 0	4 3	5 4	4 7	4 2	3 6	4 4	3 8	3 4	3 0	1 8			
取付高さ	器具間隔最大限			2 . 5	7 6	6 7	5 9	5 3	7 0	6 2	5 5	4 9	5 8	5 2	4 6	4 1	4 7	4 2	3 8	3 4	2 2				
	横方向 (A)	縦方向 (B)		3 . 0	7 9	7 1	6 4	5 8	7 2	6 5	5 9	5 3	6 0	5 5	5 0	4 5	4 9	4 5	4 1	3 7	2 4				
1 . 5m	0 m	0 m		4 . 0	8 2	7 6	7 0	6 4	7 6	7 0	6 5	6 0	6 4	5 9	5 5	5 1	5 2	4 9	4 5	4 2	2 9				
2	0	0		5 . 0	8 5	7 9	7 4	6 9	7 8	7 3	6 8	6 4	6 6	6 2	5 8	5 5	5 5	5 1	4 8	4 5	3 1				
2 . 5	0	0		7 . 0	8 8	8 3	7 9	7 5	8 1	7 7	7 3	7 0	6 9	6 6	6 3	6 0	5 7	5 5	5 2	5 0	3 5				
3	0	0		1 0 . 0	9 0	8 7	8 3	8 0	8 4	8 1	7 8	7 5	7 2	6 9	6 7	6 4	6 0	5 8	5 6	5 4	3 9				

