

屋内照明器具特性

品番 (品名)	L G B 5 0 9 2 5									
光源	L E D 2 7 0 0 _ 7 0 _ 7 5 0 x 1 7 5 0 . 0 l m									
管理番号	K 0 1 5 4 8 4 5 (0) D B 1									
B Z 分類	B Z 1 0									

器具効率 上方光束 下方光束		1 0 0 % 4 8 % 5 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
			室指数		照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 9	0 . 6	4 3	2 9	2 1	1 5	3 9	2 7	1 9	1 4	3 1	2 2	1 6	1 1	2 5	1 7	1 2	8	3
			0 . 6 7	0 . 8	5 1	3 7	2 8	2 2	4 6	3 4	2 6	2 0	3 7	2 8	2 1	1 6	3 0	2 2	1 7	1 3	6
			0 . 6 3	1 . 0	5 6	4 4	3 5	2 8	5 1	4 0	3 2	2 5	4 2	3 3	2 6	2 1	3 3	2 6	2 1	1 6	9
				1 . 2 5	6 2	5 0	4 1	3 4	5 6	4 6	3 7	3 1	4 6	3 8	3 1	2 6	3 7	3 0	2 5	2 1	1 1
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	6 6	5 5	4 6	3 9	6 0	5 0	4 2	3 6	5 0	4 2	3 5	3 0	4 0	3 3	2 8	2 4	1 4
				2 . 0	7 2	6 2	5 4	4 7	6 6	5 7	5 0	4 3	5 4	4 7	4 2	3 6	4 4	3 8	3 4	3 0	1 8
取付 高さ	器具間隔最大限			2 . 5	7 6	6 7	5 9	5 3	7 0	6 2	5 5	4 9	5 8	5 2	4 6	4 1	4 7	4 2	3 8	3 4	2 2
	横方向 (A) 縦方向 (B)			3 . 0	7 9	7 1	6 4	5 8	7 2	6 5	5 9	5 3	6 0	5 5	5 0	4 5	4 9	4 5	4 1	3 7	2 4
1 . 5 m	0 m	0 m		4 . 0	8 2	7 6	7 0	6 4	7 6	7 0	6 5	6 0	6 4	5 9	5 5	5 1	5 2	4 9	4 5	4 2	2 9
2	0	0		5 . 0	8 5	7 9	7 4	6 9	7 8	7 3	6 8	6 4	6 6	6 2	5 8	5 5	5 5	5 1	4 8	4 5	3 1
2 . 5	0	0		7 . 0	8 8	8 3	7 9	7 5	8 1	7 7	7 3	7 0	6 9	6 6	6 3	6 0	5 7	5 5	5 2	5 0	3 5
3	0	0		1 0 . 0	9 0	8 7	8 3	8 0	8 4	8 1	7 8	7 5	7 2	6 9	6 7	6 4	6 0	5 8	5 6	5 4	3 9

