

屋内照明器具特性

品番 (品名)	L G B 5 0 9 3 4									
光源	LED3500_70_1070 x1 1070.0 lm									
管理番号	K0154842 (0) DB 1									
B Z 分類	B Z 1 0									

器具効率 上方光束 下方光束		100 % 49 % 51 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
			室指数	照明率 (X0.01) Z C M																	
保守率		良 中 否	0.69	0.6	42	29	21	15	39	27	19	14	31	22	16	11	25	17	12	8	3
			0.67	0.8	50	37	28	22	46	34	26	20	37	28	21	16	29	22	17	13	6
			0.63	1.0	56	44	35	28	51	40	32	25	41	33	26	21	33	26	20	16	8
				1.25	62	50	41	34	56	46	37	31	46	37	31	26	36	30	24	20	11
下方投影面積 等価発光面積		c m ² c m ²		1.5	66	55	46	39	60	50	42	36	49	41	35	30	39	33	28	24	14
				2.0	72	62	54	47	66	57	49	43	54	47	41	36	43	38	33	29	18
取付 高さ	器具間隔最大限			2.5	76	67	59	53	69	61	55	49	57	51	46	41	46	41	37	33	21
	横方向 (A) 縦方向 (B)			3.0	78	70	64	57	72	65	59	53	60	54	49	45	48	44	40	37	24
1.5m	0 m	2.33 m		4.0	82	75	70	64	76	70	64	59	63	59	54	50	52	48	45	41	28
2	0	3		5.0	85	79	74	69	78	73	68	64	66	62	58	54	54	51	48	45	30
2.5	0	3.68		7.0	88	83	79	75	81	77	73	70	69	65	62	59	57	54	52	49	34
3	0	4.38		10.0	90	87	83	80	84	80	77	74	71	68	66	64	59	57	55	53	38

