

屋内照明器具特性	
品番 (品名)	L G B 5 0 9 6 0
光源	LED5000_70_1110 ×1 1110.0 lm
管理番号	K0154734 (0) DB 1
BZ分類	BZ6 / 0.7 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		1 6 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		8 4 %																							
保守率		良 中 否	0 . 6 9	0 . 6	5 3	4 0	3 3	2 7	5 1	3 9	3 2	2 7	4 7	3 7	3 0	2 6	4 3	3 5	2 9	2 5	2 2				
			0 . 6 7	0 . 8	6 2	5 0	4 2	3 6	6 0	4 9	4 1	3 6	5 5	4 6	3 9	3 4	5 1	4 3	3 7	3 3	3 0				
			0 . 6 3	1 . 0	6 9	5 7	4 9	4 3	6 6	5 6	4 8	4 3	6 1	5 2	4 6	4 1	5 6	4 9	4 4	3 9	3 5				
				1 . 2 5	7 4	6 4	5 7	5 1	7 2	6 2	5 5	5 0	6 6	5 8	5 2	4 8	6 1	5 5	5 0	4 6	4 1				
下方投影面積		c m ²	1 . 5	7 9	6 9	6 2	5 6	7 6	6 7	6 0	5 5	7 0	6 3	5 7	5 3	6 5	5 9	5 4	5 0	4 5					
			等価発光面積	c m ²	2 . 0	8 4	7 6	7 0	6 4	8 1	7 4	6 8	6 3	7 5	6 9	6 4	6 0	7 0	6 5	6 1	5 7	5 2			
取付高さ	器具間隔最大限		2 . 5	8 8	8 1	7 5	7 0	8 5	7 8	7 3	6 8	7 9	7 4	6 9	6 5	7 4	6 9	6 6	6 2	5 7					
	横方向 (A)	縦方向 (B)	3 . 0	9 0	8 4	7 9	7 4	8 7	8 2	7 7	7 3	8 1	7 7	7 3	6 9	7 6	7 2	6 9	6 6	6 0					
1 . 5 m	2 . 0 5 m	1 . 8 8 m	4 . 0	9 4	8 9	8 4	8 0	9 1	8 6	8 2	7 8	8 5	8 1	7 8	7 5	7 9	7 6	7 3	7 1	6 5					
2	2 . 7 2	2 . 4 8	5 . 0	9 6	9 1	8 8	8 4	9 3	8 9	8 5	8 2	8 7	8 4	8 1	7 8	8 1	7 9	7 6	7 4	6 8					
2 . 5	3 . 4 1	3 . 0 9	7 . 0	9 8	9 5	9 2	8 9	9 5	9 2	8 9	8 7	8 9	8 7	8 5	8 2	8 4	8 2	8 0	7 8	7 2					
3	4 . 0 7	3 . 7	1 0 . 0	1 0 0	9 8	9 5	9 3	9 7	9 5	9 3	9 1	9 1	8 9	8 8	8 6	8 6	8 4	8 3	8 2	7 5					

